# SN74LVC1G3157 单极双投模拟开关

## 1 特性

- ESD 保护性能超过 JESD 22 规范要求
  - 2000V 人体放电模型 (A114-A)
  - 1000V 充电器件模型 (C101)
- 1.65V 至 5.5V $V_{CC}$ 运行
- 可在 125°C 的温度下运行
- 指定的先断后合开关
- 轨到轨信号处理
- 室温下的典型工作频率为 340MHz
- 高速，典型值为 0.5ns（$V_{CC}$ = 3V，$C_L$ = 50pF）
- 低导通状态电阻，典型值约为 6Ω ($V_{CC}$ = 4.5V)
- 闩锁性能超过 100mA，符合 JESD 78 II 类规范的要求

## 2 应用

- 可穿戴设备和移动设备
- 便携式计算
- 物联网（IoT）
- 音频信号路由
- 远程无线电单元
- 便携式医疗设备
- 监控
- 家庭自动化
- I2C/SPI/UART 总线多路复用
- 无线充电

## 3 说明

该单通道单极双投 (SPDT) 模拟开关的设计工作电压范围为 1.65V 至 5.5V $V_{CC}$。


SN74LVC1G3157 器件能够同时处理模拟和数字信号。SN74LVC1G3157 器件允许在任意方向传输振幅高达 $V_{CC}$（峰值）的信号。

应用包括用于模数和数模转换系统的信号选通、斩波、调制/解调（调制解调器）以及信号多路复用。

**封装信息**

| 器件型号 | 封装 (1) | 本体尺寸（标称值） |
|---|---|---|
| SN74LVC1G3157 | SOT-23 (DBV) (6) | 2.90mm × 1.60mm |
| | SC70 (DCK) (6) | 2.00mm × 1.25mm |
| | SOT (DRL) (6) | 1.60mm × 1.20mm |
| | SON (DRY) (6) | 1.45mm × 1.00mm |
| | DSBGA (YZP) (6) | 1.41mm × 0.91mm |
| | SON (DSF) (6) | 1.00mm × 1.00mm |
| | X2SON (DTB) (6) | 0.80mm × 1.00mm |

(1) 如需了解所有可用封装，请参阅数据表末尾的可订购产品附录。




简化版原理图

本资源的原文使用英文撰写。 为方便起见，TI 提供了译文；由于翻译过程中可能使用了自动化工具，TI 不保证译文的准确性。 为确认准确性，请务必访问 ti.com 参考最新的英文版本（控制文档）。

# 内容

**1 特性** ..... 1
**2 应用** ..... 1
**3 说明** ..... 1
**4 引脚配置和功能** ..... 3
**5 规格** ..... 5
5.1 绝对最大额定值 ..... 5
5.2 热性能信息 ..... 6
5.3 ESD 等级 ..... 6
5.4 建议运行条件 ..... 6
5.5 电气特性 ..... 7
5.6 开关特性 85C（DBV、DCK） ..... 9
5.7 开关特性 125C（DBV、DCK） ..... 10
5.8 开关特性 85C（YZP、DSF、DTB、DRY、DRL） ..... 10
5.9 开关特性 125C（YZP、DSF、DTB、DRY、DRL） ..... 11
5.10 模拟通道规格 ..... 11
**6 参数测量信息** ..... 13
**7 详细说明** ..... 18
7.1 概述 ..... 18
7.2 功能方框图 ..... 18
7.3 特性说明 ..... 18
7.4 器件功能模式 ..... 18
**8 应用和实施** ..... 19
8.1 应用信息 ..... 19
8.2 典型应用 ..... 19
**9 电源相关建议** ..... 21
**10 布局** ..... 21
10.1 布局指南 ..... 21
10.2 布局示例 ..... 21
**11 器件和文档支持** ..... 22
11.1 文档支持 ..... 22
11.2 接收文档更新通知 ..... 22
11.3 支持资源 ..... 22
11.4 商标 ..... 22
11.5 静电放电警告 ..... 22
11.6 术语表 ..... 22
**12 修订历史记录** ..... 22
**13 机械、封装和可订购信息** ..... 23


Copyright © 2025 Texas Instruments Incorporated

# 4 引脚配置和功能





图 4-1. DBV 封装，6 引脚 SOT-23（顶视图）





图 4-2. DCK 封装、6 引脚 SC70（顶视图）





图 4-3. DRY 封装、6 引脚 SON（顶视图）





图 4-4. DRL 封装、6 引脚 SOT（顶视图）





图 4-5. DSF 封装、6 引脚 SON（顶视图）





图 4-6. DTB 封装、6 引脚 X2SON（顶视图）

表 4-1. 引脚功能

| 引脚 | | 类型(1) | 说明 |
|---|---|---|---|
| 名称 | SOT-23、SC70、SON、X2SON 或 SOT | | |
| B2 | 1 | I/O | 开关 I/O。将 S 设置为高电平以启用。 |
| GND | 2 | P | 接地 |
| B1 | 3 | I/O | 开关 I/O。将 S 设置为低电平以启用。 |
| A | 4 | I/O | 普通端子 |
| $V_{CC}$ | 5 | P | 电源 |
| S | 6 | I | 选择 |

(1) I = 输入；O = 输出；P = 电源

Copyright © 2025 Texas Instruments Incorporated





**图 4-7. YZP 封装 、6 引脚 DSBGA （底视图）**

| 图例 | |
|---|---|
| 输入 | 输入或输出 |
| 电源 | |

**表 4-2. 引脚功能**

| 引脚 | | 类型(1) | 说明 |
|---|---|---|---|
| 编号 | 名称 | | |
| A1 | B2 | I/O | 开关 I/O。将 S 设置为高电平以启用。 |
| A2 | S | I | 选择 |
| B1 | GND | P | 接地 |
| B2 | $V_{CC}$ | P | 电源 |
| C1 | B1 | I/O | 开关 I/O。将 S 设置为低电平以启用。 |
| C2 | A | I/O | 普通端子 |

(1) I = 输入；O = 输出；P = 电源


Copyright © 2025 Texas Instruments Incorporated

# 5 规格

## 5.1 绝对最大额定值

在自然通风条件下的工作温度范围内测得（除非另有说明）(1)

| | | 最小值 | 最大值 | 单位 |
|---|---|---|---|---|
| $V_{CC}$ | （YZP、DSF、DTB、DRY、DRL）电源电压(2) | -0.5 | 6.5 | V |
| $V_{CC}$ | （DBV、DCK）电源电压(2) | -0.5 | 6 | V |
| $V_{IN}$ | （YZP、DSF、DTB、DRY、DRL）控制输入电压(2) (3) | -0.5 | 6.5 | V |
| $V_{IN}$ | （DBV、DCK）控制输入电压(2) (3) | -0.5 | 6 | V |
| $V_{I/O}$ | 开关 I/O 电压(2) (3) (4) (5) | -0.5 | $V_{CC}$ + 0.5V | V |
| $I_{IK}$ | 控制输入钳位电流 $V_{IN}$ < 0 | -50 | | mA |
| $I_{I/OK}$ | I/O 端口二极管电流 $V_{I/O}$ < 0 或 $V_{I/O}$ > $V_{CC}$ | -50 | 50 | mA |
| $I_{I/O}$ | 导通状态开关电流(6) $V_{I/O}$ = 0 至 $V_{CC}$ | -128 | 128 | mA |
| | 通过 $V_{CC}$ 或 GND 的持续电流 | -100 | 100 | mA |
| $T_J$ | 结温 | | 150 | C |
| $T_{stg}$ | 贮存温度 | -65 | 150 | C |

(1) 应力超出“绝对最大额定值”下列出的值可能会对器件造成永久损坏。这些列出的值只是应力额定值，并不意味着器件能够在该等条件下以及在除建议工作条件以外的任何其他条件下正常运行。长时间处于绝对最大额定条件下可能会影响器件的可靠性。
(2) 除非另有说明，否则所有电压均以地为基准。
(3) 如果遵守输入和输出电流额定值，则允许超出输入负压和输出电压额定值。
(4) 该值被限制为最大 5.5V。
(5) $V_I$、$V_O$、$V_A$ 和 $V_{Bn}$ 用于表示 $V_{I/O}$ 的特定条件。
(6) $I_I$、$I_O$、$I_A$ 和 $I_{Bn}$ 用于表示 $I_{I/O}$ 的特定条件。

Copyright © 2025 Texas Instruments Incorporated

## 5.2 热性能信息

| 热指标 | | SN74LVC1G3157 | | | | | | 单位 |
|---|---|---|---|---|---|---|---|---|
| | | DBV (SOT-23) | DCK (SC70) | DRL (SOT) | DRY (SON) | DTB (X2SON) | YZP (DSBGA) | |
| | | 6 引脚 | 6 引脚 | 6 引脚 | 6 引脚 | 6 引脚 | 6 引脚 | |
| $R_{\theta JA}$ | 结至环境热阻 | 258.2 | 286.4 | 244.1 | 284.2 | 324.5 | 129.4 | °C/W |
| $R_{\theta JC(top)}$ | 结至外壳（顶部）热阻 | 182.8 | 224.6 | 112.5 | 138.6 | 150.5 | 1.9 | °C/W |
| $R_{\theta JB}$ | 结至电路板热阻 | 142.8 | 143.7 | 109.9 | 170.9 | 239.0 | 40.0 | °C/W |
| $\Psi_{JT}$ | 结至顶部特征参数 | 118.4 | 124.5 | 9.3 | 13.7 | 17.2 | 0.6 | °C/W |
| $\Psi_{JB}$ | 结至电路板特征参数 | 142.2 | 142.8 | 109.3 | 167.9 | 238.3 | 40.2 | °C/W |

## 5.3 ESD 等级

| | | | 值 | 单位 |
|---|---|---|---|---|
| $V_{(ESD)}$ | 静电放电 | 人体放电模型 (HBM)，符合 ANSI/ESDA/JEDEC JS-001 标准(1) | ±2000 | V |
| | | 充电器件模型 (CDM)，符合 JEDEC 规范 JESD22-C101(2) | ±1000 | V |

(1) JEDEC 文档 JEP155 指出：500V HBM 支持在标准 ESD 控制流程下安全生产。
(2) JEDEC 文档 JEP157 指出：250V CDM 能够在标准 ESD 控制流程下安全生产。

## 5.4 建议运行条件

在自然通风条件下的工作温度范围内测得（除非另有说明）(1)

| | | | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|
| $V_{CC}$ | 电源电压 | | 1.65 | | 5.5 | V |
| $V_{I/O}$ | 开关输入或输出电压（$V_{CC}$ 的最大值） | | 0 | | $V_{CC}$ | V |
| $V_{IN}$ | 控制输入电压 | | 0 | | 5.5 | V |
| $V_{IH}$ | 高电平输入电压，控制输入 | $V_{CC}$ = 1.65V 至 1.95V | $V_{CC}$ * 0.75 | | | V |
| | | $V_{CC}$ = 2.3V 至 5.5V | $V_{CC}$ * 0.7 | | | V |
| $V_{IL}$ | 低电平输入电压，控制输入 | $V_{CC}$ = 1.65V 至 1.95V | | | $V_{CC}$ * 0.25 | V |
| | | $V_{CC}$ = 2.3V 至 5.5V | | | $V_{CC}$ * 0.3 | V |
| $\Delta t/\Delta v$ | 输入转换上升或下降速率 | $V_{CC}$ = 1.8 ± 0.15V | | | 20 | ns/V |
| | | $V_{CC}$ = 2.5 ± 0.2V | | | 20 | |
| | | $V_{CC}$ = 3.3V ± 0.3V | | | 10 | |
| | | $V_{CC}$ = 5V ± 0.5V | | | 10 | |
| $T_A$ | 自然通风条件下的工作温度范围 | BGA 封装 (YZP) | -40 | | 85 | °C |
| | | 所有其他封装（DBV、DCK、DRL、DRY、DSF） | -40 | | 125 | |

(1) 器件所有的未使用输入必须保持在 VCC 或 GND 以确保器件正常运行。请参阅 TI 应用报告 CMOS 输入缓慢或悬空的影响 (SCBA004)


Copyright © 2025 Texas Instruments Incorporated

## 5.5 电气特性

在自然通风条件下的工作温度范围内测得（除非另有说明）(1)

| 参数 | | 测试条件 | | | | 最小值 | 典型值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|---|
| **SN74LVC1G3157** | | | | | | | | | |
| | | $V_{CC}$ V | $V_{I/O}$ V | $I_O$ mA | $T_A$ | | | | |
| $r_{ON}$ | 导通状态开关电阻(2) | 1.65 | $V_I$ = 0V | $I_O$ = 4mA | 25°C | | 11 | | Ω |
| | | | | | -40°C 至 +85°C | | | 20 | |
| | | | | | -40°C 至 +125°C | | | 20 | |
| | | | $V_I$ = 1.65 | $I_O$ = -4mA | 25°C | | 15 | | |
| | | | | | -40°C 至 +85°C | | | 50 | |
| | | | | | -40°C 至 +125°C | | | 50 | |
| | | 2.3 | $V_I$ = 0V | $I_O$ = 8mA | 25°C | | 8 | | |
| | | | | | -40°C 至 +85°C | | | 12 | |
| | | | | | -40°C 至 +125°C | | | 12 | |
| | | | $V_I$ = 2.3V | $I_O$ = -8mA | 25°C | | 11 | | |
| | | | | | -40°C 至 +85°C | | | 30 | |
| | | | | | -40°C 至 +125°C | | | 30 | |
| | | 3 | $V_I$ = 0V | $I_O$ = 24mA | 25°C | | 7 | | |
| | | | | | -40°C 至 +85°C | | | 9 | |
| | | | | | -40°C 至 +125°C | | | 9 | |
| | | | $V_I$ = 3V | $I_O$ = -24mA | 25°C | | 9 | | |
| | | | | | -40°C 至 +85°C | | | 20 | |
| | | | | | -40°C 至 +125°C | | | 20 | |
| | | 4.5 | $V_I$ = 0V | $I_O$ = 30mA | 25°C | | 6 | | |
| | | | | | -40°C 至 +85°C | | | 7 | |
| | | | | | -40°C 至 +125°C | | | 7 | |
| | | | $V_I$ = 2.4V | $I_O$ = 30mA | 25°C | | 7 | | |
| | | | | | -40°C 至 +85°C | | | 12 | |
| | | | | | -40°C 至 +125°C | | | 12 | |
| | | | $V_I$ = 4.5V | $I_O$ = -30mA | 25°C | | 7 | | |
| | | | | | -40°C 至 +85°C | | | 15 | |
| | | | | | -40°C 至 +125°C | | | 15 | |
| $r_{range}$ | （YZP、DSF、DTB、DRY、DRL）信号范围内的导通状态开关电阻(2) (3) | 1.65 | 0 ≤ $V_{Bn}$ ≤ $V_{CC}$ | $I_A$ = -4mA | 25°C | | 140 | | Ω |
| | | | | | -40°C 至 +85°C | | | 140 | |
| | | | | | -40°C 至 +125°C | | | 140 | |
| | | 2.3 | | $I_A$ = -8mA | 25°C | | 45 | | |
| | | | | | -40°C 至 +85°C | | | 45 | |
| | | | | | -40°C 至 +125°C | | | 45 | |
| | | 3 | | $I_A$ = -24mA | 25°C | | 18 | | |
| | | | | | -40°C 至 +85°C | | | 18 | |
| | | | | | -40°C 至 +125°C | | | 18 | |
| | | 4.5 | | $I_A$ = -30mA | 25°C | | 10 | | |
| | | | | | -40°C 至 +85°C | | | 10 | |
| | | | | | -40°C 至 +125°C | | | 10 | |

Copyright © 2025 Texas Instruments Incorporated

在自然通风条件下的工作温度范围内测得（除非另有说明）(1)

| 参数 | | 测试条件 | | | | 最小值 | 典型值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|---|
| $r_{range}$ | （DBV、DCK）信号范围内的导通状态开关电阻(2) (3) | 1.65 | 0 ≤ $V_{Bn}$ ≤ $V_{CC}$ | $I_A$ = -4mA | 25°C | | | 200 | Ω |
| | | | | | -40°C 至 +85°C | | | 200 | |
| | | | | | -40°C 至 +125°C | | | 200 | |
| | | 2.3 | | $I_A$ = -8mA | 25°C | | | 65 | |
| | | | | | -40°C 至 +85°C | | | 65 | |
| | | | | | -40°C 至 +125°C | | | 65 | |
| | | 3 | | $I_A$ = -24mA | 25°C | | | 25 | |
| | | | | | -40°C 至 +85°C | | | 25 | |
| | | | | | -40°C 至 +125°C | | | 25 | |
| | | 4.5 | | $I_A$ = -30mA | 25°C | | | 15 | |
| | | | | | -40°C 至 +85°C | | | 15 | |
| | | | | | -40°C 至 +125°C | | | 15 | |
| $\Delta r_{ON}$ | 任何两个通道之间的最大导通电阻 (2) (4) (5) | 1.65 | $V_{Bn}$ = 1.15V | $I_A$ = -4mA | 25°C | | 0.5 | | Ω |
| | | | | | -40°C 至 +85°C | | 0.5 | | |
| | | | | | -40°C 至 +125°C | | 0.5 | | |
| | | 2.3 | $V_{Bn}$ = 1.6V | $I_A$ = -8mA | 25°C | | 0.1 | | |
| | | | | | -40°C 至 +85°C | | 0.1 | | |
| | | | | | -40°C 至 +125°C | | 0.3 | | |
| | | 3 | $V_{Bn}$ = 2.1V | $I_A$ = -24mA | 25°C | | 0.1 | | |
| | | | | | -40°C 至 +85°C | | 0.1 | | |
| | | | | | -40°C 至 +125°C | | 0.3 | | |
| | | 4.5 | $V_{Bn}$ = 3.15V | $I_A$ = -30mA | 25°C | | 0.1 | | |
| | | | | | -40°C 至 +85°C | | 0.1 | | |
| | | | | | -40°C 至 +125°C | | 0.2 | | |
| $r_{on(flat)}$ | 导通电组平坦度(2) (4) (6) | 1.65 | 0 ≤ $V_{Bn}$ ≤ $V_{CC}$ | $I_A$ = -4mA | 25°C | | 110 | | Ω |
| | | | | | -40°C 至 +85°C | | 110 | | |
| | | | | | -40°C 至 +125°C | | 110 | | |
| | | 2.3 | | $I_A$ = -8mA | 25°C | | 26 | | |
| | | | | | -40°C 至 +85°C | | 26 | | |
| | | | | | -40°C 至 +125°C | | 40 | | |
| | | 3 | | $I_A$ = -24mA | 25°C | | 9 | | |
| | | | | | -40°C 至 +85°C | | 9 | | |
| | | | | | -40°C 至 +125°C | | 10 | | |
| | | 4.5 | | $I_A$ = -30mA | 25°C | | 4 | | |
| | | | | | -40°C 至 +85°C | | 4 | | |
| | | | | | -40°C 至 +125°C | | 5 | | |
| $I_{off}$ (7) | 关断漏电流 | 1.65 至 5.5 | 0 ≤ $V_I$ , $V_O$ ≤ $V_{CC}$ | | 25°C | | ±0.05 | ±0.1 | μA |
| | | | | | -40°C 至 +85°C | | | ±1 | |
| | | | | | -40°C 至 +125°C | | | ±1 | |
| $I_{S(on)}$ | 导通状态开关漏电流 | 5.5 | $V_I$ = $V_{CC}$ 或 GND，$V_O$ = 开路 | | 25°C | | | ±0.1 | μA |
| | | | | | -40°C 至 +85°C | | | ±1 | |
| | | | | | -40°C 至 +125°C | | | ±1 | |


Copyright © 2025 Texas Instruments Incorporated

在自然通风条件下的工作温度范围内测得（除非另有说明）(1)

| 参数 | | 测试条件 | | | 最小值 | 典型值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $I_{IN}$ | 控制输入电流 | 0 至 5.5 | 0 ≤ $V_{IN}$ ≤ $V_{CC}$ | 25°C | | ±0.05 | ±0.1 | μA |
| | | | | -40°C 至 +85°C | | | ±1 | |
| | | | | -40°C 至 +125°C | | | ±1 | |
| $I_{CC}$ | 电源电流 | 5.5 | S = $V_{CC}$ 或 GND | 25°C | | | 1 | μA |
| | | | | -40°C 至 +85°C | | | 10 | |
| | | | | -40°C 至 +125°C | | | 35 | |
| $\Delta I_{CC}$ | 静态器件电流，$I_{DD}$ 最大值 | 5.5 | S = $V_{CC}$ - 0.6V | 25°C | | | 500 | μA |
| | | | | -40°C 至 +85°C | | | 500 | |
| | | | | -40°C 至 +125°C | | | 500 | |
| $C_I$ | 控制输入电容 | 5 | S (VDD/2) | 25°C | | 2.7 | | pF |
| | | | | -40°C 至 +85°C | | 2.7 | | |
| | | | | -40°C 至 +125°C | | 2.7 | | |
| $C_{io(off)}$ | 开关输入/输出电容 | 5 | Bn (VDD/2) | 25°C | | 5.2 | | pF |
| | | | | -40°C 至 +85°C | | 5.2 | | |
| | | | | -40°C 至 +125°C | | 5.2 | | |
| $C_{io(on)}$ | 开关输入/输出电容 | 5 | Bn (VDD/2) | 25°C | | 17.3 | | pF |
| | | | | -40°C 至 +85°C | | 17.3 | | |
| | | | | -40°C 至 +125°C | | 17.3 | | |
| | | | A (VDD/2) | 25°C | | 17.3 | | |
| | | | | -40°C 至 +85°C | | 17.3 | | |
| | | | | -40°C 至 +125°C | | 17.3 | | |

(1) $T_A$ = 25C
(2) 在通过开关的指示电流下由 I/O 引脚之间的电压降测量。通态电阻由两个（A 或 B）端口上的较低电压决定。
(3) 根据设计确定
(4) $\Delta r_{on} = r_{on(max)} - r_{on(min)}$，在相同的 $V_{CC}$、温度或电压电平下测得
(5) 此参数已表征，但未经生产测试。
(6) 平坦度定义为在指定条件范围内导通状态电阻的最大值和最小值之间的差异。
(7) $I_{off}$ 与 $I_{S(off)}$ 相同（关断状态开关漏电流）。

## 5.6 开关特性 85C（DBV、DCK）

$T_A$ = -40 至 +85℃

| 参数 | | 从（输入） | 至（输出） | $V_{CC}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $t_{pd}$ | $R_L$ = 250 Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | A 或 Bn | Bn 或 A | 1.8V ± 0.15V | | | 2 | ns |
| | | | | 2.5V ± 0.2V | | | 1.2 | |
| | | | | 3.3V ± 0.3V | | | 0.8 | |
| | | | | 5V ± 0.5V | | | 0.3 | |
| $t_{en}$ | $R_L$ = 250 Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | S | Bn | 1.8V ± 0.15V | 5 | | 24 | ns |
| | | | | 2.5V ± 0.2V | 3.5 | | 14 | |
| | | | | 3.3V ± 0.3V | 2.5 | | 7.6 | |
| | | | | 5V ± 0.5V | 1.7 | | 5.7 | |
| $t_{dis}$ | $R_L$ = 250 Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$，$V_▲$ = 0.3V | | | 1.8V ± 0.15V | 3 | | 13 | |
| | | | | 2.5V ± 0.2V | 2 | | 7.5 | |
| | | | | 3.3V ± 0.3V | 1.5 | | 6 | |
| | | | | 5V ± 0.5V | 0.8 | | 5 | |

Copyright © 2025 Texas Instruments Incorporated

$T_A$ = -40 至 +85℃

| 参数 | | 从（输入） | 至（输出） | $V_{CC}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $T_{B-M}$ | 先断后合时间 | | | 1.8V ± 0.15V | 0.5 | | | ns |
| | | | | 2.5V ± 0.2V | 0.5 | | | |
| | | | | 3.3V ± 0.3V | 0.5 | | | |
| | | | | 5V ± 0.5V | 0.5 | | | |

## 5.7 开关特性 125C（DBV、DCK）

$T_A$ = -40 至 +125℃

| 参数 | | 从（输入） | 至（输出） | $V_{CC}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $t_{pd}$ | $R_L$ = 250Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | A 或 Bn | Bn 或 A | 1.8V ± 0.15V | | | 2 | ns |
| | | | | 2.5V ± 0.2V | | | 1.2 | |
| | | | | 3.3V ± 0.3V | | | 0.8 | |
| | | | | 5V ± 0.5V | | | 0.5 | |
| $t_{en}$ | $R_L$ = 250Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | S | Bn | 1.8V ± 0.15V | 1 | | 24.5 | ns |
| | | | | 2.5V ± 0.2V | 1 | | 14.5 | |
| | | | | 3.3V ± 0.3V | 2.5 | | 8 | |
| | | | | 5V ± 0.5V | 1.7 | | 7 | |
| $t_{dis}$ | $R_L$ = 250Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$，$V_▲$ = 0.3V | | | 1.8V ± 0.15V | 2.5 | | 13.5 | |
| | | | | 2.5V ± 0.2V | 2 | | 8 | |
| | | | | 3.3V ± 0.3V | 1.5 | | 6.5 | |
| | | | | 5V ± 0.5V | 0.8 | | 5 | |
| $T_{B-M}$ | 先断后合时间 | | | 1.8V ± 0.15V | 0.5 | | | ns |
| | | | | 2.5V ± 0.2V | 0.5 | | | |
| | | | | 3.3V ± 0.3V | 0.5 | | | |
| | | | | 5V ± 0.5V | 0.5 | | | |

## 5.8 开关特性 85C（YZP、DSF、DTB、DRY、DRL）

$T_A$ = -40 至 +85℃

| 参数 | | 从（输入） | 至（输出） | $V_{CC}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $t_{pd}$ | $R_L$ = 500Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | A 或 Bn | Bn 或 A | 1.8V ± 0.15V | | | 2 | ns |
| | | | | 2.5V ± 0.2V | | | 1.2 | |
| | | | | 3.3V ± 0.3V | | | 0.8 | |
| | | | | 5V ± 0.5V | | | 0.3 | |
| $t_{en}$ | $R_L$ = 500Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | S | Bn | 1.8V ± 0.15V | 7 | | 24 | ns |
| | | | | 2.5V ± 0.2V | 3.5 | | 14 | |
| | | | | 3.3V ± 0.3V | 2.5 | | 7.6 | |
| | | | | 5V ± 0.5V | 1.7 | | 5.7 | |
| $t_{dis}$ | $R_L$ = 500Ω、$C_L$ = 50pF、$V_{load}$ = $V_{CC}$、$V_△$ = 0.3V | | | 1.8V ± 0.15V | 3 | | 13 | |
| | | | | 2.5V ± 0.2V | 2 | | 7.5 | |
| | | | | 3.3V ± 0.3V | 1.5 | | 5.3 | |
| | | | | 5V ± 0.5V | 0.8 | | 3.8 | |


Copyright © 2025 Texas Instruments Incorporated

$T_A$ = -40 至 +85℃

| 参数 | | 从（输入） | 至（输出） | $V_{CC}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $T_{B-M}$ | 先断后合时间 | | | 1.8V ± 0.15V | 0.5 | | | ns |
| | | | | 2.5V ± 0.2V | 0.5 | | | |
| | | | | 3.3V ± 0.3V | 0.5 | | | |
| | | | | 5V ± 0.5V | 0.5 | | | |

## 5.9 开关特性 125C（YZP、DSF、DTB、DRY、DRL）

$T_A$ = -40 至 +125℃

| 参数 | | 从（输入） | 至（输出） | $V_{CC}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| $t_{pd}$ | $R_L$ = 500Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | A 或 Bn | Bn 或 A | 1.8V ± 0.15V | | | 2 | ns |
| | | | | 2.5V ± 0.2V | | | 1.2 | |
| | | | | 3.3V ± 0.3V | | | 0.8 | |
| | | | | 5V ± 0.5V | | | 0.5 | |
| $t_{en}$ | $R_L$ = 500Ω，$C_L$ = 50pF，$V_{load}$ = $V_{CC}$ | S | Bn | 1.8V ± 0.15V | 1 | | 24.5 | ns |
| | | | | 2.5V ± 0.2V | 1 | | 14.5 | |
| | | | | 3.3V ± 0.3V | 2.5 | | 8 | |
| | | | | 5V ± 0.5V | 1.7 | | 6 | |
| $t_{dis}$ | $R_L$ = 500Ω、$C_L$ = 50pF、$V_{load}$ = $V_{CC}$、$V_{Δ}$ = 0.3V | | | 1.8V ± 0.15V | 2.5 | | 13.5 | |
| | | | | 2.5V ± 0.2V | 2 | | 8 | |
| | | | | 3.3V ± 0.3V | 1.5 | | 5.5 | |
| | | | | 5V ± 0.5V | 0.8 | | 4 | |
| $T_{B-M}$ | 先断后合时间 | | | 1.8V ± 0.15V | 0.5 | | | ns |
| | | | | 2.5V ± 0.2V | 0.5 | | | |
| | | | | 3.3V ± 0.3V | 0.5 | | | |
| | | | | 5V ± 0.5V | 0.5 | | | |

## 5.10 模拟通道规格

在自然通风条件下的工作温度范围内测得（除非另有说明）

| 参数 | 从（输入） | 至（输出） | 测试条件 | $v_{cc}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| 频率响应（开关导通）(1) | A 或 Bn | Bn 或 A | $R_L$ = 50Ω，$f_{in}$ = 正弦波 | 1.65V | | 340 | | MHz |
| | | | | 2.3V | | 340 | | |
| | | | | 3V | | 340 | | |
| | | | | 4.5V | | 340 | | |
| 串扰（开关间）(2) | B1 或 B2 | B2 或 B1 | $R_L$ = 50Ω，$f_{in}$ = 10MHz（正弦波） | 1.65V | | -54 | | dB |
| | | | | 2.3V | | -54 | | |
| | | | | 3V | | -54 | | |
| | | | | 4.5V | | -54 | | |
| 馈通衰减（开关关闭）(2) | A 或 Bn | Bn 或 A | $C_L$ = 5pF，$R_L$ = 50Ω，$f_{in}$ = 10MHz（正弦波） | 1.65V | | -57 | | dB |
| | | | | 2.3V | | -57 | | |
| | | | | 3V | | -57 | | |
| | | | | 4.5V | | -57 | | |
| 电荷注入 | S (Vs = VDD/2) | A | $C_L$ = 0.1nF，$R_L$ = 1MΩ | 3.3V | | 3 | | pC |
| | | | | 5V | | 7 | | |

Copyright © 2025 Texas Instruments Incorporated

在自然通风条件下的工作温度范围内测得（除非另有说明）

| 参数 | 从（输入） | 至（输出） | 测试条件 | $v_{cc}$ | 最小值 | 标称值 | 最大值 | 单位 |
|---|---|---|---|---|---|---|---|---|
| 总谐波失真（YZP、DSF、DTB、DRY、DRL） | A 或 Bn | Bn 或 A | $V_I$ = 1.4$V_{p-p}$，Vbias = Vcc/2，$R_L$ = 10kΩ，$f_{in}$ = 600Hz 至 20kHz（正弦波） | 1.65V | | 0.1 | | % |
| 总谐波失真（DBV、DCK） | A 或 Bn | Bn 或 A | $V_I$ = 1.4$V_{p-p}$，Vbias = Vcc/2，$R_L$ = 10kΩ，$f_{in}$ = 600Hz 至 20kHz（正弦波） | 1.65V | | 0.5 | | % |
| 总谐波失真 | A 或 Bn | Bn 或 A | $V_I$ = 2.0$V_{p-p}$，Vbias = Vcc/2，$R_L$ = 10kΩ，$f_{in}$ = 600Hz 至 20kHz（正弦波） | 2.3V | | 0.025 | | % |
| | | | | 3V | | 0.015 | | |
| | | | | 4.5V | | 0.01 | | |

(1) 将 fin 设置为 0dBm 并提供 0.4V 的偏压。增大 fin 频率，直到增益低于插入损耗 3dB。
(2) 将 fin 设置为 0dBm 并提供 0.4V 的偏压。


Copyright © 2025 Texas Instruments Incorporated

# 6 参数测量信息






图 6-1. 导通电阻测试电路




Condition 1: $V_I$ = GND, $V_O$ = $V_{CC}$
Condition 2: $V_I$ = $V_{CC}$, $V_O$ = GND

图 6-2. 关断状态开关漏电流测试电路






图 6-3. 导通状态开关漏电流测试电路


Copyright © 2025 Texas Instruments Incorporated





LOAD CIRCUIT

| TEST | S1 |
|---|---|
| $t_{PLH}/t_{PHL}$ | Open |
| $t_{PLZ}/t_{PZL}$ | $V_{LOAD}$ |
| $t_{PHZ}/t_{PZH}$ | GND |


| $V_{CC}$ | INPUTS | | $V_M$ | $V_{LOAD}$ | $C_L$ | $R_L$ | $V_\Delta$ |
|---|---|---|---|---|---|---|---|
| | $V_I$ | $t_r/t_f$ | | | | | |
| 1.8 V ± 0.15 V | $V_{CC}$ | ≤2 ns | $V_{CC}/2$ | 2 × $V_{CC}$ | 50 pF | 500 Ω | 0.3 V |
| 2.5 V ± 0.2 V | $V_{CC}$ | ≤2 ns | $V_{CC}/2$ | 2 × $V_{CC}$ | 50 pF | 500 Ω | 0.3 V |
| 3.3 V ± 0.3 V | $V_{CC}$ | ≤2.5 ns | $V_{CC}/2$ | 2 × $V_{CC}$ | 50 pF | 500 Ω | 0.3 V |
| 5 V ± 0.5 V | $V_{CC}$ | ≤2.5 ns | $V_{CC}/2$ | 2 × $V_{CC}$ | 50 pF | 500 Ω | 0.3 V |





VOLTAGE WAVEFORMS
PULSE DURATION




VOLTAGE WAVEFORMS
SETUP AND HOLD TIMES




VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES
INVERTING AND NONINVERTING OUTPUTS




VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES
LOW- AND HIGH-LEVEL ENABLING

NOTES: A. $C_L$ includes probe and jig capacitance.
B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
C. All input pulses are supplied by generators having the following characteristics: PRR ≤ 10 MHz, $Z_O$ = 50 Ω.
D. The outputs are measured one at a time, with one transition per measurement.
E. $t_{PLZ}$ and $t_{PHZ}$ are the same as $t_{dis}$.
F. $t_{PZL}$ and $t_{PZH}$ are the same as $t_{en}$.
G. $t_{PLH}$ and $t_{PHL}$ are the same as $t_{pd}$.
H. All parameters and waveforms are not applicable to all devices.

**图 6-4. 负载电路和电压波形**


Copyright © 2025 Texas Instruments Incorporated





图 6-5. 频率响应（开关导通）





图 6-6. 串扰（开关间）





图 6-7. 馈通





图 6-8. 电荷注入测试


Copyright © 2025 Texas Instruments Incorporated





图 6-9. 总谐波失真





图 6-10. 先断后合内部时序

# 7 详细说明

## 7.1 概述

SN74LVC1G3157 器件是一种单极双投 (SPDT) 模拟开关，设计工作电压范围为 1.65V 至 5.5V $V_{CC}$。SN74LVC1G3157 器件能够处理模拟和数字信号。该器件允许在任意方向传输振幅高达 $V_{CC}$（峰值）的信号。

## 7.2 功能方框图





图 7-1. 逻辑图（正逻辑）

## 7.3 特性说明

由 1.65V 至 5.5V 电源供电使该器件能在由不同逻辑电平组成的许多不同系统中运行，从而实现轨到轨信号切换。根据控制输入激活 B1 通道或 B2 通道。如果控制输入为低电平，则选择 B1 通道。如果控制输入为高电平，则选择 B2 通道。

## 7.4 器件功能模式

表 7-1 列出了选择其中一个控制输入时的导通通道。

表 7-1. 功能表

| 控制<br>输入 | 导通<br>通道 |
|---|---|
| L | B1 |
| H | B2 |


Copyright © 2025 Texas Instruments Incorporated

# 8 应用和实施

**备注**

以下应用部分中的信息不属于 TI 器件规格的范围，TI 不担保其准确性和完整性。TI 的客 户应负责确定器件是否适用于其应用。客户应验证并测试其设计，以确保系统功能。

## 8.1 应用信息

SN74LVC1G3157 SPDT 模拟开关足够灵活，可用于各种电路，例如模拟音频路由、加电监视器、内存共享等。有关应用的详细信息，请参阅 SN74LVC1G3157 和 SN74LVC2G53 SPDT 模拟开关。

## 8.2 典型应用





**图 8-1. 典型应用原理图**

### *8.2.1 设计要求*

输入可以是模拟输入或数字输入，但 TI 建议在施加任何信号之前等待 $V_{CC}$ 上升到 *节 5.4* 中的电平。应根据信号类型和规格使用适当的终端电阻器。选择引脚不应悬空；上拉或下拉时使用可由 GPIO 过驱动的电阻器。

Copyright © 2025 Texas Instruments Incorporated

### 8.2.2 详细设计过程

使用此电路创意，系统设计人员可以确保组件或子系统电源在允许信号施加到其输入之前斜升。这对于没有过压耐受输入的集成电路很有用。基本思路是在 VCC1 电源轨上使用电阻分压器，该分压器正在斜升。电阻分压器的 RC 时间常数进一步延迟了 SPDT 总线开关选择引脚上的电压斜坡。通过仔细选择 R1、R2 和 C 的值，可以确保 VCC1 在从 A 到 B2 的路径建立之前达到其标称值，从而防止在器件/系统上电之前 I/O 上出现信号通电。为了确保实现所需的极低延迟，设计人员应使用方程式 1 来计算从接地转换 (0V) 到电源电压 (VCC1/2) 一半所需的时间。

$$\text{Set}\left(\frac{R2}{R1+R2}\times V_{CC1} > V_{IH}\right)\text{of the select pin} \tag{1}$$

选择 Rs 和 C 以获得所需的延迟。当 $V_S$ 变为高电平时，信号将被传递。

### 8.2.3 应用曲线





图 8-2. $V_S$ 电压斜坡


Copyright © 2025 Texas Instruments Incorporated

# 9 电源相关建议

大多数系统有一个常见的 3.3V 或 5V 电源轨，可为该器件的 $V_{CC}$ 引脚供电。如果这不可用，则可以使用开关模式电源 (SMPS) 或线性压差稳压器 (LDO) 从另一个电压轨为该器件供电。

# 10 布局

## 10.1 布局指南

TI 建议使信号线路尽可能短。TI 还建议在信号线长度大于 1 英寸时采用微带线或带状线技术。根据应用的要求，这些布线的特征阻抗必须设计为 50Ω 或 75Ω。不要将此器件放置在离高压开关元件太近的地方，因为它们可能会干扰器件。

## 10.2 布局示例





**图 10-1. 推荐布局示例**

# 11 器件和文档支持

## 11.1 文档支持

### *11.1.1 相关文档*

请参阅如下相关文档：

- 德州仪器 (TI)，*慢速或浮点 CMOS 输入的影响*
- 德州仪器 (TI)，*SN74LVC1G3157 和 SN74LVC2G53 SPDT 模拟开关*

## 11.2 接收文档更新通知

要接收文档更新通知，请导航至 ti.com 上的器件产品文件夹。点击*通知* 进行注册，即可每周接收产品信息更改摘要。有关更改的详细信息，请查看任何已修订文档中包含的修订历史记录。

## 11.3 支持资源

TI E2E™ 中文支持论坛是工程师的重要参考资料，可直接从专家处获得快速、经过验证的解答和设计帮助。搜索现有解答或提出自己的问题，获得所需的快速设计帮助。

链接的内容由各个贡献者“按原样”提供。这些内容并不构成 TI 技术规范，并且不一定反映 TI 的观点；请参阅 TI 的使用条款。

## 11.4 商标

TI E2E™ is a trademark of Texas Instruments.
所有商标均为其各自所有者的财产。

## 11.5 静电放电警告



静电放电 (ESD) 会损坏这个集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

## 11.6 术语表

TI 术语表　　本术语表列出并解释了术语、首字母缩略词和定义。

# 12 修订历史记录

注：以前版本的页码可能与当前版本的页码不同

| Changes from Revision N (May 2025) to Revision O (June 2025) | Page |
|---|---|
| • 将相关 DBV 和 DCK 规格与其他封装分离 | 5 |

| Changes from Revision M (August 2022) to Revision N (May 2025) | Page |
|---|---|
| • 绝对最大电源电压已更改 | 5 |
| • 更新了 DBV 和 DCK 的热参数 | 6 |
| • 更新了 $r_{range}$ | 7 |
| • 更新了 85°C 1.8V 和 125°C 5V 条件下的启用时序 | 9 |
| • 更新了 85°C 5V 和 125°C 3.3V、5V 条件下的禁用时序 | 9 |
| • 更新了 THD 测试条件和 1.65V 规格 | 11 |


Copyright © 2025 Texas Instruments Incorporated

**Changes from Revision L (May 2017) to Revision M (August 2022)** **Page**

- 更新了整个文档中的表格、图和交叉参考的编号格式.....1
- 更新了 *引脚配置和功能* 部分.....3
- 更新了 *详细设计过程* 部分中的公式.....20

**Changes from Revision K (January 2017) to Revision L (May 2017)** **Page**

- 删除了 *特性* 中的“用于模拟和数字应用”.....1
- 删除了 *特性* 中的“高度线性”.....1
- 将 *说明* 中的第一句从“该单极双投 (SPDT)...”更改为：“该单通道单极双投 (SPDT)...”.....1
- 向 *器件信息* 添加了 X2SON (DTB) 封装.....1
- 向 *引脚配置和功能* 添加了 X2SON (DTB 封装.....3
- 更改了图 6-2，从 SW1 = $V_{IL}$ 更新为 SW1 = $V_{IH}$，从 SW2 = $V_{IH}$ 更新为：SW2 = $V_{IL}$.....13
- 更改了图 6-5.....13
- 在图 6-6 中的 B1 上添加了一个串联 50Ω 电阻器.....13
- 更改了图 6-7.....13

**Changes from Revision J (June 2016) to Revision K (January 2017)** **Page**

- 向 *应用* 部分添加了新的应用.....1

**Changes from Revision I (June 2015) to Revision J (June 2016)** **Page**

- 删除了 *特性* 中的 200V 机器模型 (A115-A).....1
- 将 *特性* 从“室温下的典型工作频率为 300MHz”更改为“室温下的典型工作频率为 340MHz”.....1
- 更新了 *器件信息* 表.....1
- 更新了所有封装的引脚排列图.....3
- 添加了 *接收文档更新通知* 部分.....22

**Changes from Revision H (May 2012) to Revision I (June 2015)** **Page**

- 添加了 *器件信息* 表、*引脚配置和功能* 部分、*ESD 等级* 表、*特性说明* 部分、*器件功能模式* 部分、*应用和实施* 部分、*电源相关建议* 部分、*布局* 部分、*器件和文档支持* 部分以及 *机械、封装和可订购信息* 部分.....1
- 更新了 *特性*.....1

**Changes from Revision G (September 2011) to Revision H (May 2012)** **Page**

- 使用正确的引脚标签更改了 YZP。.....3

## 13 机械、封装和可订购信息

下述页面包含机械、封装和订购信息。这些信息是指定器件可用的最新数据。数据如有变更，恕不另行通知，且不会对此文档进行修订。有关此数据表的浏览器版本，请查阅左侧的导航栏。

Copyright © 2025 Texas Instruments Incorporated

## PACKAGING INFORMATION

| Orderable part number | Status (1) | Material type (2) | Package \| Pins | Package qty \| Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|---|---|---|---|---|---|---|---|---|---|
| 74LVC1G3157DBVR1G4 | Active | Production | SOT-23 (DBV) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | CC55 |
| 74LVC1G3157DBVR1G4.A | Active | Production | SOT-23 (DBV) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | CC55 |
| 74LVC1G3157DBVR1G4.B | Active | Production | SOT-23 (DBV) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | CC55 |
| 74LVC1G3157DRLRG4 | Active | Production | SOT-5X3 (DRL) \| 6 | 4000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C57 |
| 74LVC1G3157DRLRG4.B | Active | Production | SOT-5X3 (DRL) \| 6 | 4000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C57 |
| 74LVC1G3157DSFRG4 | Active | Production | SON (DSF) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| 74LVC1G3157DSFRG4.B | Active | Production | SON (DSF) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| SN74LVC1G3157DBVR | Active | Production | SOT-23 (DBV) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU \| SN | Level-1-260C-UNLIM | -40 to 125 | (3HRH, CC55, CC5F, CC5K, CC5R) CC5S |
| SN74LVC1G3157DBVR.A | Active | Production | SOT-23 (DBV) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | (3HRH, CC55, CC5F, CC5K, CC5R) CC5S |
| SN74LVC1G3157DBVR.B | Active | Production | SOT-23 (DBV) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | (3HRH, CC55, CC5F, CC5K, CC5R) CC5S |
| SN74LVC1G3157DCK3 | Obsolete | Production | SC70 (DCK) \| 6 | - | - | Call TI | Call TI | -40 to 125 | C5Z |
| SN74LVC1G3157DCKR | Active | Production | SC70 (DCK) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU \| SN | Level-1-260C-UNLIM | -40 to 125 | (3HSH, C55, C5F, C5J, C5R) |
| SN74LVC1G3157DCKR.A | Active | Production | SC70 (DCK) \| 6 | 3000 \| LARGE T&R | Yes | SN | Level-1-260C-UNLIM | -40 to 125 | (3HSH, C55, C5F, C5J, C5R) |
| SN74LVC1G3157DCKR.B | Active | Production | SC70 (DCK) \| 6 | 3000 \| LARGE T&R | Yes | SN | Level-1-260C-UNLIM | -40 to 125 | (3HSH, C55, C5F, C5J, C5R) |
| SN74LVC1G3157DRLR | Active | Production | SOT-5X3 (DRL) \| 6 | 4000 \| LARGE T&R | Yes | NIPDAU \| NIPDAUAG | Level-1-260C-UNLIM | -40 to 125 | (C57, C5R) |
| SN74LVC1G3157DRLR.A | Active | Production | SOT-5X3 (DRL) \| 6 | 4000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | (C57, C5R) |
| SN74LVC1G3157DRLR.B | Active | Production | SOT-5X3 (DRL) \| 6 | 4000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | (C57, C5R) |
| SN74LVC1G3157DRY2 | Obsolete | Production | SON (DRY) \| 6 | - | - | Call TI | Call TI | -40 to 125 | C5 |
| SN74LVC1G3157DRYR | Active | Production | SON (DRY) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| SN74LVC1G3157DRYR.A | Active | Production | SON (DRY) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| SN74LVC1G3157DRYR.B | Active | Production | SON (DRY) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| SN74LVC1G3157DSFR | Active | Production | SON (DSF) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU \| NIPDAUAG | Level-1-260C-UNLIM | -40 to 125 | C5 |

| Orderable part number | Status (1) | Material type (2) | Package \| Pins | Package qty \| Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|---|---|---|---|---|---|---|---|---|---|
| SN74LVC1G3157DSFR.A | Active | Production | SON (DSF) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| SN74LVC1G3157DSFR.B | Active | Production | SON (DSF) \| 6 | 5000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | C5 |
| SN74LVC1G3157DTBR | Active | Production | X2SON (DTB) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | 7X |
| SN74LVC1G3157DTBR.B | Active | Production | X2SON (DTB) \| 6 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 125 | 7X |
| SN74LVC1G3157YZPR | Active | Production | DSBGA (YZP) \| 6 | 3000 \| LARGE T&R | Yes | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | C5N |
| SN74LVC1G3157YZPR.B | Active | Production | DSBGA (YZP) \| 6 | 3000 \| LARGE T&R | Yes | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | C5N |

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF SN74LVC1G3157 :**


- Automotive : SN74LVC1G3157-Q1

NOTE: Qualified Version Definitions:


- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects

## TAPE AND REEL INFORMATION

**REEL DIMENSIONS**





**TAPE DIMENSIONS**




| | |
|---|---|
| A0 | Dimension designed to accommodate the component width |
| B0 | Dimension designed to accommodate the component length |
| K0 | Dimension designed to accommodate the component thickness |
| W | Overall width of the carrier tape |
| P1 | Pitch between successive cavity centers |

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**





*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 74LVC1G3157DBVR1G4 | SOT-23 | DBV | 6 | 3000 | 180.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| 74LVC1G3157DRLRG4 | SOT-5X3 | DRL | 6 | 4000 | 180.0 | 8.4 | 2.0 | 1.8 | 0.75 | 4.0 | 8.0 | Q3 |
| 74LVC1G3157DSFRG4 | SON | DSF | 6 | 5000 | 180.0 | 8.4 | 1.16 | 1.16 | 0.5 | 4.0 | 8.0 | Q2 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 180.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 180.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 178.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 178.0 | 9.0 | 3.23 | 3.17 | 1.37 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 178.0 | 9.2 | 3.3 | 3.23 | 1.55 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DCKR | SC70 | DCK | 6 | 3000 | 178.0 | 9.2 | 2.4 | 2.4 | 1.22 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DCKR | SC70 | DCK | 6 | 3000 | 180.0 | 8.4 | 2.3 | 2.55 | 1.2 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DCKR | SC70 | DCK | 6 | 3000 | 178.0 | 9.0 | 2.4 | 2.5 | 1.2 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DRLR | SOT-5X3 | DRL | 6 | 4000 | 180.0 | 8.4 | 1.98 | 1.78 | 0.69 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DRLR | SOT-5X3 | DRL | 6 | 4000 | 180.0 | 8.4 | 2.0 | 1.8 | 0.75 | 4.0 | 8.0 | Q3 |
| SN74LVC1G3157DRYR | SON | DRY | 6 | 5000 | 180.0 | 9.5 | 1.2 | 1.65 | 0.7 | 4.0 | 8.0 | Q1 |
| SN74LVC1G3157DRYR | SON | DRY | 6 | 5000 | 180.0 | 9.5 | 1.15 | 1.6 | 0.75 | 4.0 | 8.0 | Q1 |
| SN74LVC1G3157DRYR | SON | DRY | 6 | 5000 | 180.0 | 8.4 | 1.2 | 1.65 | 0.69 | 4.0 | 8.0 | Q1 |

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| SN74LVC1G3157DSFR | SON | DSF | 6 | 5000 | 180.0 | 9.5 | 1.16 | 1.16 | 0.5 | 4.0 | 8.0 | Q2 |
| SN74LVC1G3157DSFR | SON | DSF | 6 | 5000 | 180.0 | 8.4 | 1.16 | 1.16 | 0.5 | 4.0 | 8.0 | Q2 |
| SN74LVC1G3157DSFR | SON | DSF | 6 | 5000 | 180.0 | 8.4 | 1.16 | 1.16 | 0.63 | 4.0 | 8.0 | Q2 |
| SN74LVC1G3157DTBR | X2SON | DTB | 6 | 3000 | 180.0 | 9.5 | 0.94 | 1.13 | 0.41 | 2.0 | 8.0 | Q2 |
| SN74LVC1G3157YZPR | DSBGA | YZP | 6 | 3000 | 178.0 | 9.2 | 1.02 | 1.52 | 0.63 | 4.0 | 8.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---|---|---|---|---|---|---|---|
| 74LVC1G3157DBVR1G4 | SOT-23 | DBV | 6 | 3000 | 210.0 | 185.0 | 35.0 |
| 74LVC1G3157DRLRG4 | SOT-5X3 | DRL | 6 | 4000 | 210.0 | 185.0 | 35.0 |
| 74LVC1G3157DSFRG4 | SON | DSF | 6 | 5000 | 210.0 | 185.0 | 35.0 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 210.0 | 185.0 | 35.0 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 210.0 | 185.0 | 35.0 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 208.0 | 191.0 | 35.0 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74LVC1G3157DBVR | SOT-23 | DBV | 6 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74LVC1G3157DCKR | SC70 | DCK | 6 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74LVC1G3157DCKR | SC70 | DCK | 6 | 3000 | 210.0 | 185.0 | 35.0 |
| SN74LVC1G3157DCKR | SC70 | DCK | 6 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74LVC1G3157DRLR | SOT-5X3 | DRL | 6 | 4000 | 202.0 | 201.0 | 28.0 |
| SN74LVC1G3157DRLR | SOT-5X3 | DRL | 6 | 4000 | 210.0 | 185.0 | 35.0 |
| SN74LVC1G3157DRYR | SON | DRY | 6 | 5000 | 189.0 | 185.0 | 36.0 |
| SN74LVC1G3157DRYR | SON | DRY | 6 | 5000 | 184.0 | 184.0 | 19.0 |
| SN74LVC1G3157DRYR | SON | DRY | 6 | 5000 | 200.0 | 183.0 | 25.0 |
| SN74LVC1G3157DSFR | SON | DSF | 6 | 5000 | 184.0 | 184.0 | 19.0 |
| SN74LVC1G3157DSFR | SON | DSF | 6 | 5000 | 210.0 | 185.0 | 35.0 |

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---|---|---|---|---|---|---|---|
| SN74LVC1G3157DSFR | SON | DSF | 6 | 5000 | 183.0 | 183.0 | 20.0 |
| SN74LVC1G3157DTBR | X2SON | DTB | 6 | 3000 | 189.0 | 185.0 | 36.0 |
| SN74LVC1G3157YZPR | DSBGA | YZP | 6 | 3000 | 220.0 | 220.0 | 35.0 |




# PACKAGE OUTLINE

## DRL0006A

## SOT - 0.6 mm max height

PLASTIC SMALL OUTLINE




NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. Reference JEDEC registration MO-293 Variation UAAD

# EXAMPLE BOARD LAYOUT


## DRL0006A

## SOT - 0.6 mm max height

PLASTIC SMALL OUTLINE




LAND PATTERN EXAMPLE
SCALE:30X




SOLDERMASK DETAILS

4223266/F 11/2024

NOTES: (continued)


5. Publication IPC-7351 may have alternate designs.
6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.
7. Land pattern design aligns to IPC-610, Bottom Termination Component (BTC) solder joint inspection criteria.

# EXAMPLE STENCIL DESIGN

## DRL0006A

## SOT - 0.6 mm max height

PLASTIC SMALL OUTLINE




SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:30X

4223266/F 11/2024

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# PACKAGE OUTLINE

## DBV0006A

## SOT-23 - 1.45 mm max height


SMALL OUTLINE TRANSISTOR





4214840/G 08/2024

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.25 per side.
4. Leads 1,2,3 may be wider than leads 4,5,6 for package orientation.
5. Refernce JEDEC MO-178.




LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:15X





SOLDER MASK DETAILS

4214840/G 08/2024

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE:15X

4214840/G 08/2024

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# PACKAGE OUTLINE

## YZP0006

## DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY




D: Max = 1.418 mm, Min =1.357 mm


E: Max = 0.918 mm, Min =0.857 mm

4219524/A 06/2014


NOTES:

NanoFree Is a trademark of Texas Instruments.

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. NanoFree™ package configuration.




LAND PATTERN EXAMPLE
SCALE:40X





SOLDER MASK DETAILS
NOT TO SCALE

4219524/A 06/2014

NOTES: (continued)

4. Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SBVA017 (www.ti.com/lit/sbva017).




SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:40X

4219524/A 06/2014

NOTES: (continued)


5. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

# PACKAGE OUTLINE

## DCK0006A

## SOT - 1.1 max height


SMALL OUTLINE TRANSISTOR





4214835/D 11/2024

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
4. Falls within JEDEC MO-203 variation AB.




LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:18X





SOLDER MASK DETAILS

4214835/D 11/2024

NOTES: (continued)

5. Publication IPC-7351 may have alternate designs.
6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SOLDER PASTE EXAMPLE
BASED ON 0.125 THICK STENCIL
SCALE:18X

4214835/D 11/2024

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.


# DRY 6 USON - 0.6 mm max height

PLASTIC SMALL OUTLINE - NO LEAD




Images above are just a representation of the package family, actual package may vary.
Refer to the product data sheet for package details.


# DRY0006A



# PACKAGE OUTLINE


## USON - 0.6 mm max height

PLASTIC SMALL OUTLINE - NO LEAD





NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.




LAND PATTERN EXAMPLE
1:1 RATIO WITH PKG SOLDER PADS
EXPOSED METAL SHOWN
SCALE:40X




SOLDER MASK DETAILS

4222894/A 01/2018

NOTES: (continued)


3. For more information, see QFN/SON PCB application report in literature No. SLUA271 (www.ti.com/lit/slua271).

# EXAMPLE STENCIL DESIGN

## DRY0006A

## USON - 0.6 mm max height

PLASTIC SMALL OUTLINE - NO LEAD




SOLDER PASTE EXAMPLE
BASED ON 0.075 - 0.1 mm THICK STENCIL
SCALE:40X

4222894/A 01/2018

NOTES: (continued)


4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

# PACKAGE OUTLINE

## DRY0006B


## USON - 0.55 mm max height

PLASTIC SMALL OUTLINE - NO LEAD





NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.




LAND PATTERN EXAMPLE
1:1 RATIO WITH PKG SOLDER PADS
SCALE:40X




SOLDER MASK DETAILS

4222207/B 02/2016

NOTES: (continued)


3. For more information, see QFN/SON PCB application report in literature No. SLUA271 (www.ti.com/lit/slua271).

# EXAMPLE STENCIL DESIGN

## DRY0006B

## USON - 0.55 mm max height

PLASTIC SMALL OUTLINE - NO LEAD




SOLDER PASTE EXAMPLE
BASED ON 0.075 - 0.1 mm THICK STENCIL
SCALE:40X

4222207/B 02/2016

NOTES: (continued)


4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

# PACKAGE OUTLINE

## DSF0006A

## X2SON - 0.4 mm max height


PLASTIC SMALL OUTLINE - NO LEAD





4220597/B 06/2022

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC registration MO-287, variation X2AAF.




LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:40X




SOLDER MASK DETAILS

4220597/B 06/2022

NOTES: (continued)


4. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).

# EXAMPLE STENCIL DESIGN

## DSF0006A

## X2SON - 0.4 mm max height

PLASTIC SMALL OUTLINE - NO LEAD




SOLDER PASTE EXAMPLE
BASED ON 0.09 mm THICK STENCIL

PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE
SCALE:40X

4220597/B 06/2022


4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

# DTB0006A

# PACKAGE OUTLINE

## X2SON - 0.35 mm max height


PLASTIC SMALL OUTLINE - NO LEAD




4223406/C 02/2019

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. The package thermal pads must be soldered to the printed circuit board for optimal thermal and mechanical performance.
4. The size and shape of this feature may vary.
5. Features may not exist. Recommend use of pin 1 marking on top of package for orientation purposes.





LAND PATTERN EXAMPLE
SOLDER MASK DEFINED
SCALE:50X

4223406/C 02/2019

NOTES: (continued)

6. This package is designed to be soldered to a thermal pads on the board. For more information, see Texas Instruments literature number SLUA271 (www.ti.com/lit/slua271).
7. Vias are optional depending on application, refer to device data sheet. If some or all are implemented, recommended via locations are shown.




SOLDER PASTE EXAMPLE
BASED ON 0.07 mm THICK STENCIL

PRINTED SOLDER COVERAGE BY AREA UNDER PACKAGE
SCALE:50X

4223406/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.

# 重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做出任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 TI 销售条款)、TI 通用质量指南 或 ti.com 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。 除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2026，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月