A product Line of
Diodes Incorporated

PI6C485311

3.3V Low Skew 1-to-2 Differential to LVPECL Fanout Buffer


Features

- Pin-to-pin compatible to ICS85311
- Maximum operation frequency: 800MHz
- 2 pair of differential LVPECL outputs
- CLK, nCLK pair accepts LVDS, LVPECL, LVHSTL, SSTL and HCSL input level
- Output Skew: 100ps (maximum)
- Part-to-part skew: 150ps (maximum)
- Propagation delay: 2ns (maximum)
- 3.3V power supply
- Operating Temperature: -40°C to 85°C
- Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)
- Halogen and Antimony Free. "Green" Device (Note 3)
- For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please contact us or your local Diodes representative.
  https://www.diodes.com/quality/product-definitions/
- Packaging (Pb-free & Green avaliable):
  - 8-pin SOIC (W)
  - 8-pin MSOP (U)

Description

The PI6C485311 is a high-performance low-skew LVPECL fanout buffer. PI6C485311 features two selectable differential inputs and translates to four LVPECL ultra-low jitter outputs. The inputs can also be configured to single-ended with external resistor bias circuit. The CLK input accepts LVPECL or LVDS or LVHSTL or SSTL or HCSL signals, and PCLK input accepts LVPECL or SSTL or CML signals. PI6C485311 is ideal for differential to LVPECL translations and/or LVPECL clock distribution. Typical clock translation and distribution applications are data-communications and telecommunications.


Block Diagram



Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

® Diodes Incorporated

Pin Configuration



Pin Description

Name	Pin #	Type	Description
V_{EE}	5	P	Connect to Negative power supply
CLK	7	I_PD	Non-inverting differential clock input
$_{n}$CLK	6	I_PU	Inverting differential clock input
V_{CC}	8	P	Connect to 3.3V.
Q_1, $_{n}Q_1$	3.4	O	Differential output pair, LVPECL interface level.
Q_0, $_{n}Q_0$	1,2	O	Differential output pair, LVPECL interface level.

Note:
1. I = Input, O = Output, P = Power supply connection, I_PD = Input with pull down, I_PU = Input with pull up

Pin Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
C_{IN}	Input Capacitance				4	pF
R_pullup	Input Pullup Resistance			50		KΩ
R_pulldown	Input Pulldown Resistance			50		

® Diodes Incorporated

Maximum Ratings (Above which the useful life may be impaired. For user guidelines, not tested)

Storage Temperature ..... -55 to +150°C
Supply Voltage to Ground Potential (V_{DD}, V_{DDO}) .-0.5 to +4.6V
Inputs (Referenced to GND).....-0.5 to V_{DD}+0.5V
Clock Output (Referenced to GND).....-0.5 to V_{DD}+0.5V
Latch up 200mA
ESD Protection (Input)..... 2000V min (HBM)
Junction Temperature .....150 °C max

Note:

Stresses greater than those listed under MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

Operating Conditions

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
V_{CC}	Power Supply Voltage		3.0	3.3	3.6	V
T_A	Ambient Temperature		-40		85	°C
I_{EE}	Power Supply Current	500 MHz			60	mA

Differential DC Input Characteristics (T_A = -40°C to 85°C, V_{CC} = 3.0V to 3.6V unless otherwise stated.)

Symbol	Parameter		Conditions	Min.	Typ.	Max.	Units
I_{IH}	Input High Current	$_n$CLK	V_{IN} = V_{CC} = 3.6V			5	uA
		CLK	V_{IN} = V_{CC} = 3.6V			150	uA
I_{IL}	Input Low Current	$_n$CLK	V_{CC} = 3.6V, V_{IN} = 0V	-150			uA
		CLK	V_{CC} = 3.6V, V_{IN} = 0V	-5			uA
V_{PP}	Peak-to-peak Voltage			0.15		1.3	V
V_{CMR}	Common Mode Input Voltage(1, 2)			V_{EE}+0.5		V_{CC}-0.85V	V

Notes:
1. For single ended applications, the maximum input voltage for CLK and nCLK is V_{CC}+0.3V
2. Common mode voltage is defined as V_{IH}.

LVPECL DC Characteristics

(T_A = -40°C to 85°C, V_{CC} = 3.0V to 3.6V, R_L= 50Ω to V_{CC} - 2V, unless otherwise stated below.)

Symbol	Parameter		Conditions	Min.	Typ.	Max.	Units
I_{IH}	Input High Current	$_n$CLK	V_{IN} = V_{CC} = 3.6V			5	µA
		CLK	V_{IN} = V_{CC} = 3.6V			150	
I_{IL}	Input Low Current	$_n$CLK	V_{CC} = 3.6V, V_{IN} = 0V	-150			
		CLK	V_{CC} = 3.6V, V_{IN} = 0V	-5			
V_{PP}	Peak-to-peak Voltage			0.3		1	V
V_{CMR}	Common Mode Input Voltage; Note(1,2)			V_{EE}+1.5		V_{CC}	
V_{OH}	Output High Voltage			V_{CC}-1.4		V_{CC}-0.9	
V_{OL}	Output Low Voltage			V_{CC}-2.0		V_{CC}-1.6	
V_{SWING}	Peak-to-peak Output Voltage Swing			0.6		1.0	

Notes:
1. For single ended applications, the maximum input voltage for PCLK and $_n$PCLK is V_{CC}+0.3V.
2. Common mode voltage is defined as V_{IH}.

® Diodes Incorporated

AC Characteristics[1] (T_A = -40°C to 85°C, V_{CC} = 3.0V to 3.6V, R_L= 50Ω to V_{CC} - 2V, unless otherwise stated below.)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
f_{max}	Output Frequency				800	MHz
t_{Pd}	Propagation Delay[2]		1.0		2.0	ns
Tsk(o)	Output-to-output Skew[3]				100	ps
Tsk(pp)	Part-to-part Skew[4]				150	
t_r/t_f	Output Rise/Fall time	20% - 80%	75		300	
odc	Output duty cycle		40		60	%

Notes:

1. All parameters are measured at 500MHz unless noted otherwise
2. Measured from the V_{CC}/2 of the input to the differential output crossing point
3. Defined as skew between outputs at the same supply voltage and with equal load condition. Measured at the outputs differential crossing point.
4. Defined as skew between outputs on different parts operating at the same supply voltage and with equal load condition. Measured at the outputs differential crossing point.

® Diodes Incorporated

Applications Information

Wiring the differential input to accept single ended levels

Figure 1 shows how the differential input can be wired to accept single ended levels. The reference voltage V_REF = V_{DD}/2 is generated by the bias resistors R1, R2 and C1. This bias circuit should be located as close as possible to the input pin. The ratio of R1 and R2 might need to be adjusted to position the V_REF in the center of the input voltage swing. For example, if the input clock swing is only 2.5V and V_{DD} = 3.3V, V_REF should be 1.25V and R1/R2 = 0.609.




Figure 1: Single-ended Signal Driving Differential Input

Part Marking

W Package

PI6C
485311WE
AYWXX

A: Die Rev
YW: Year & Workweek
1st X: Assembly Code
2nd X: Fab Code


U Package


Top mark not available at this time. To obtain advance information regarding the top mark, please contact your local sales representative.

® Diodes Incorporated


Packaging Mechanical


8-SOIC (W)






SYMBOLS	MIN.	NOM.	MAX.
A	—	—	1.75
A1	0.10	—	0.25
A2	1.25	—	—
b	0.31	—	0.51
c	0.10	—	0.25
D	4.80	4.90	5.00
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e		1.27 BSC	
L	0.40	—	1.27
h	0.25	—	0.50
θ°	0	—	8







Recommended Land Pattern

NOTE :
1. ALL DIMENSIONS ARE IN mm. ANGLES IN DEGREES
2. DIMENSIONS EXCLUDE BURRS, MOLD FLASH OR PROTRUSIONS
3. REFER JEDEC MS-012
4. RECOMMENDED LAND PATTERN IS FOR REFERENCE ONLY.

20-1273

DATE: 06/02/20


DESCRIPTION: 8-Pin, 150mil-Wide, SOIC


PACKAGE CODE: W (W8)

DOCUMENT CONTROL #: PD-1001 **REVISION: H**

® Diodes Incorporated


8-MSOP (U)





PKG DIMENSIONS(MM)		
SYMBOL	Min.	Max.
A	--	1.10
A1	0.00	0.15
A2	0.75	0.95
b	0.22	0.38
c	0.08	0.23
D	2.80	3.20
E	4.65	5.15
E1	2.80	3.20
e	0.65 BSC	
L	0.40	0.80
L1	0.95 REF	
θ	0°	8°

RECOMMENDED LAND PATTERN(unit:mm)



NOTE:
1. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES IN DEGREES.
2. REFER JEDEC MO-187F/AA
3. PACKAGE OUTLINE DIMENSIONS DO NOT INCLUDE MOLD FLASH AND METAL BURR.
4. LAND PATTERN REFERENCE DIODES MSOP-8 PACKAGE INFORMATION.

DATE: 11/04/19

DESCRIPTION: 8-Pin, Mini Small Outline Package, MSOP

PACKAGE CODE: U (U8)

DOCUMENT CONTROL #: PD-1261 REVISION: H

For latest package info.

please check: http://www.diodes.com/design/support/packaging/pericom-packaging/packaging-mechanicals-and-thermal-characteristics/

Ordering Information

Ordering Code	Package Code	Package Description
PI6C485311WEX	W	8-pin, 150mil-Wide (SOIC)
PI6C485311UEX	U	8-pin, Mini Small Outline Package (MSOP)

Notes:

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. E = Pb-free and Green
5. X suffix = Tape/Reel

® Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2020, Diodes Incorporated

www.diodes.com