









Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:30mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:-40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V-0)
Standard: PBT
Max.Processing Temp: 180°C for 30-60 seconds
(200°C for 10 seconds)

Dimension antitheses list	
ITEM	A
Standard	4.00

Ordering Information

HC-CZ 254 - * - N - Z - * - ** - *

- No.of Rows: 2=Dual Row, 3=Three Row, 4=Four Row
- No.of Pins: 10/16/20Pin, 32/44/48Pin, 64Pin
- Type: Z=直针 W=弯针
- Length (Plastic): (塑高)
- Contact Plating: G0:Gold Flash, G1:1u" Gold, G2:3u" Gold, G3:5u" Gold, G4:10u" Gold, G5:15u" Gold, G6:30u" Gold, S0:Gold Flash/Tin, S1:Tin
- Contact Type: F=Female, M=male

深圳市华灿天禄电子有限公司 工程专用章

序号 No.	变更内容 MODIFY CONTENT	日 期 MODIFY DATE
1	初版发行	

GENERL TOLERANCE		制 图 DRAWING	
DIM	TOL	审 核 CHECK	
X.X	±0.30	批 准 APPROVAL	
X.XX	±0.20	比 例 SCALE	
X.XXX	±0.10	投 影 Projection	
Angle	±3.0°		

深圳市华灿天禄电子有限公司
ShenzhenhuacantianluELECTRONICS CO.,LTD

产品名称 TITLE	欧式插座2.54 双排 直母	版 本 REV.	A
产品料号 PART NO.	HC-CZ254-2-N-Z-11.5-XX-F	单 位 UNITS	mm
材 料 MATERIAL		页 次 SHEET	1/1