DATASHEET

Opto Interrupter
ITR8102



Features
- Fast response time
- High sensitivity
- Pb free
- This product itself will remain within RoHS compliant version
- Compliance with EU REACH

Description
- The ITR8102 consist of an infrared emitting diode and a silicon phototransistor, encased side-by-side on converging optical axis in a black thermoplastic housing
- The phototransistor receives radiation from the IR LED only .This is the normal situation. When an object is in between, phototransistor could not receives the radiation.
- For additional component information, please refer to IR908-7C and PT908-7C.

Applications
- Mouse Copier
- Switch Scanner
- Floppy disk driver
- Non-contact Switching
- For Direct Board

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7
Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

Device Selection Guide

Part Category	Chip Material	Lens Color
IR908-7C	GaAs	Water Clear
PT908-7C	Silicon	Water Clear

Absolute Maximum Ratings (Ta=25˚C)

Parameter		Symbol	Ratings	Unit
Input	Power Dissipation at (or below) 25˚C Free Air Temperature	P_d	75	mW
	Reverse Voltage	V_R	5	V
	Forward Current	I_F	50	mA
Output	Collector Power Dissipation	P_C	75	mW
	Collector Current	I_C	20	mA
	Collector-Emitter Voltage	BV_{CEO}	30	V
	Emitter-Collector Voltage	BV_{ECO}	5	V
Operating Temperature		Topr	-25~+85	˚C
Storage Temperature		Tstg	-40~+85	˚C
Lead Soldering Temperature (*1) (3 mm from the package)		Tsol	260	˚C

Note: (*1) Soldering time < 5 sec.

Electro-Optical Characteristics (Ta=25˚C)


Parameter		Symbol	Min.	Typ.	Max.	Unit	Conditions
Input	Forward Voltage	V_F	---	1.25	1.60	V	I_F=20mA
	Reverse Current	I_R	---	---	10	μA	V_R=5V
	Peak Wavelength	λ_P	---	940	---	nm	I_F=20mA
Output	Dark Current	I_{CEO}	---	---	100	nA	V_{CE}=20V Ee=0mW/cm^2
	C-E Saturation Voltage	$V_{CE(sat)}$	---	---	0.4	V	I_C=0.9mA I_F=20mA
Transfer Characteristics	Collect Current	$I_{C(ON)}$	0.9	---	15	mA	V_{CE}=5V I_F=20mA
	Rise time	tr	---	15	---	μsec	V_{CE}=5V，I_C=1mA R_L=1KΩ
	Fall time	tf	---	15	---	μsec	

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7


Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

Typical Electro-Optical Characteristics Curves for IR


Forward Current vs. Ambient Temperature



Spectral Distribution




Forward Current vs. Forward Voltage



Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7
Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

Typical Electro-Optical Characteristics Curves for PT


Spectral Sensitivity



EVERLIGHT

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7
Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

Package Dimension




Notes:
1. All dimensions are in millimeters
2. Tolerances unless dimensions ±0.3mm
3. Lead spacing is measured where the lead emerge from the package or under stopper.

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7
Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

Packing Quantity Specification

1. 100pcs/Tube, 20Tubes/Box
2. 4 Boxes/Carton

Label Form Specification



- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- LOT No: Lot Number

Notes

Lead Forming

1. During lead frame bending, the lead frame should be bent at a distance more than 3mm from bottom of the epoxy.
   Note: Must fix lead frame and do not touch epoxy before bending to avoid Photo Interrupter broken.
2. Lead forming should be done before soldering.
3. Avoid stressing the Photo Interrupter package during leads forming. The stress to the base may damage the characteristics of Photo Interrupter, or it may break the Photo Interrupter.
4. Cut the Photo Interrupter lead frame at room temperature. Cutting the lead frame at high temperatures may cause failure of the Photo Interrupter.
5. When mounting the Photo Interrupter onto a PCB, the PCB holes must be aligned exactly with the lead position of the Photo Interrupter. If the Photo Interrupter are mounted with stress at the leads, it causes deterioration of the epoxy resin and this will degrade the Photo Interrupter.

Storage

1. The Photo Interrupter should be stored at 10~30°C and 70%RH or less after being shipped from Everlight and the storage life limits are 3 months. If the Photo Interrupter are stored for 3 months or more, they can be stored at 10°C~25°C and 20%RH~60%RH for a year in a sealed container with a nitrogen atmosphere. After opening the package, the devices must be stored at 10°C~25°C and 20%RH~60%RH, and suggested to be used within 24 hours or as soon as possible. Besides, suggest that the remaining devices seal in the package bag as soon as possible please.
2. Please avoid rapid transitions in ambient temperature, especially in high humidity environments where condensation can occur.

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7


Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

Soldering

1. Careful attention should be paid during soldering. When soldering, leave more than 3mm from solder joint to epoxy bulb, and soldering beyond the base of the tie bar is recommended.
2. Recommended soldering conditions:

Hand Soldering		DIP Soldering	
Temp. at tip of iron	300°C Max. (30W Max.)	Preheat temp.	100°C Max. (60 sec Max.)
Soldering time	3 sec Max.	Bath temp. & time	260 Max., 5 sec Max
Distance	3mm Min.(From solder joint to epoxy bulb)	Distance	3mm Min. (From solder joint to epoxy bulb)

3. Recommended soldering profile



4. Avoiding applying any stress to the lead frame while the Photo Interrupter are at high temperature particularly when soldering.
5. Dip and hand soldering should not be done more than one time
6. After soldering the Photo Interrupter, the epoxy bulb should be protected from mechanical shock or vibration until the Photo Interrupter return to room temperature.
7. A rapid-rate process is not recommended for cooling the Photo Interrupter down from the peak temperature.
8. Although the recommended soldering conditions are specified in the above table, dip or hand soldering at the lowest possible temperature is desirable for the Photo Interrupter.
9. Wave soldering parameter must be set and maintain according to recommended temperature and dwell time in the solder wave.

Cleaning

Do not clean the Photo Interrupter by the ultrasonic.

Heat Management

1. Heat management of Photo Interrupter must be taken into consideration during the design stage of Photo Interrupter application. The current should be de-rated appropriately by referring to the de-rating curve found in each product specification.
2. The temperature surrounding the Photo Interrupter in the application should be controlled.

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7
Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)

ESD (Electrostatic Discharge)

1. The products are sensitive to static electricity or surge voltage. ESD can damage a die and its reliability.
2. When handling the products, the following measures against electrostatic discharge are strongly recommended:
   Eliminating the charge
   Grounded wrist strap, ESD footwear, clothes and floors
   Grounded workstation equipment and tools
   ESD table/shelf mat made of conductive materials
3. Proper grounding is required for all devices, equipment, and machinery used in product assembly. Surge protection should be considered when designing of commercial products.
4. If tools or equipment contain insulating materials such as glass or plastic, the following measures against electrostatic discharge are strongly recommended:
   Dissipating static charge with conductive materials
   Preventing charge generation with moisture
   Neutralizing the charge with ionizers

DISCLAIMER

1. EVERLIGHT reserves the right(s) on the adjustment of product material mix for the specification.
2. The product meets EVERLIGHT published specification for a period of twelve (12) months from date of shipment.
3. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
4. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from the use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
5. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without obtaining EVERLIGHT's prior consent.
6. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.

Copyright © 2010, Everlight All Rights Reserved. Release Date : 2019/7/24. Issue No: DRX-0000139 Rev.7

Ver.:7 Release Date:07/30/2019 狀態:Approved(正式發行)