
BC846/BC847/BC848

NPN Plastic-Encapsulate Transistors


Features

- Ideally suited for automatic insertion
- For switching and AF amplifier applications



1. BASE
2. EMITTER
3. COLLECTOR

SOT-23



Ordering Information

Product ID	Pack	Marking	Qty(PCS)
BC846/BC847 /BC848	SOT-23	1x	3000

x: BC846A=A; BC846B=B; BC846C=C;
BC847A=E; BC847B=F; BC847C=G;
BC848A=J; BC848B=K; BC848C=L.


Maxmim Ratings (Ta=25℃unless otherwise noted)


Symbol	Parameter		Limit	Unit
V_{CBO}	Collector-Base Voltage	BC846	80	V
		BC847	50	
		BC848	30	
V_{CEO}	Collector-Emitter Voltage	BC846	65	V
		BC847	45	
		BC848	30	
V_{EBO}	Emitter-Base Voltage		6	V
I_C	Collector Current		100	mA
P_C	Collector Power Dissipation		200	mW
$R_{\Theta JA}$	Thermal Resistance From Junction To Ambient		625	℃/W
T_j	Junction Temperature		150	℃
T_{stg}	Storage Temperature		-55～+150	℃


Electrcal Charcteristics (Ta=25℃unless otherwise specified)


Symbol	Parameter		Test conditions	Min	Max	Unit
$V_{(BR)CBO}$	Collector-base breakdown voltage	BC846 BC847 BC848	I_C=10μA, I_E=0	80 50 30		V
$V_{(BR)CEO}$	Collector-emitter breakdown voltage	BC846 BC847 BC848	I_C=10mA, I_B=0	65 45 30		V
$V_{(BR)EBO}$	Emitter-base breakdown voltage		I_E=10μA, I_C=0	6		V
I_{CBO}	Collector cut-off current	BC846 BC847 BC848	V_{CB}=70V, I_E=0 V_{CB}=50V, I_E=0 V_{CB}=30V, I_E=0		100	nA
I_{EBO}	Emitter cut-off current		V_{EB}=5V, I_C=0		100	nA
h_{FE}	DC current gain	BC846A BC847A BC848A BC846B BC847B BC848B BC846C BC847C BC848C	V_{CE}=5V, I_C=2mA	110 200 420	220 450 800	
$V_{CE(sat)}$	Collector-emitter saturation voltage		I_C=100mA, I_B=5mA		0.5	V
$V_{BE(sat)}$	Base-emitter saturation voltage				1.1	V
f_T	Transition frequency		V_{CE}=5V, I_C=10mA, f=30MHz	100		MHz
Cob	Collector output capacitance		V_{CB} =10V,f= 1MHz		4.5	pF


Typical Characteristics









V_{BEsat} — I_C
β=20
T_a=25℃
T_a=100 ℃
BASE-EMITTER SATURATION VOLTAGE V_{BEsat} (mV)
COLLECTOR CURREMT I_C (mA)


V_{CEsat} — I_C
β=20
T_a=100 ℃
T_a=25℃
COLLECTOR-EMITTER SATURATION VOLTAGE V_{CEsat} (mV)
COLLECTOR CURREMT I_C (mA)



I_C — V_{BE}
COMMON EMITTER
V_{CE}=5V
T_a=100℃
T_a=25℃
COLLECTOR CURRENT I_C (mA)
BASE-EMMITER VOLTAGE V_{BE} (V)



f_T — I_C
COMMON EMITTER
V_{CE}=5V
T_a=25℃
TRANSITION FREQUENCY f_T (MHz)
COLLECTOR CURRENT I_C (mA)



C_{ob}/C_{ib} — V_{CB}/V_{EB}
f=1MHz
I_E=0/I_C=0
T_a=25 ℃
C_{ib}
C_{ob}
CAPACITANCE C (pF)
REVERSE VOLTAGE V (V)


P_C — T_a
COLLECTOR POWER DISSIPATION P_C (mW)
AMBIENT TEMPERATURE T_a (℃)

SOT-23 Package Outline Dimensions








Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

Attention

■ Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.

■ HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.

■ Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

■ HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could
give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.

■ In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

■ No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.

■ Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

■ Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.