# SN74AUC1G32 Single 2-Input Positive-OR Gate

## 1 Features

- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Protection Exceeds JESD 22
  - 2000-V Human-Body Model (A114-A)
  - 1000-V Charged-Device Model (C101)
- Available in the Texas Instruments NanoFree™ Package
- Optimized for 1.8-V Operation and Is 3.6-V I/O Tolerant to Support Mixed-Mode Signal Operation
- $I_{off}$ Partial-Power-Down Mode and Back Drive Protection
- Sub-1-V Operable
- Max $t_{pd}$ of 2.4 ns at 1.8 V
- Low Power Consumption, 10-μA Maximum $I_{CC}$
- ±8-mA Output Drive at 1.8 V

## 2 Applications

- AV Receiver
- Audio Dock: Portable
- Blu-ray Player and Home Theater
- Embedded PC
- MP3 Player/Recorder (Portable Audio)
- Personal Digital Assistant (PDA)
- Power: Telecom/Server AC/DC Supply: Single Controller: Analog and Digital
- Solid State Drive (SSD): Client and Enterprise
- TV: LCD/Digital and High-Definition (HDTV)
- Tablet: Enterprise
- Video Analytics: Server
- Wireless Headset, Keyboard, and Mouse

## 3 Description

This single 2-input positive-OR gate is operational at 0.8-V to 2.7-V $V_{CC}$, but is designed specifically for 1.65-V to 1.95-V $V_{CC}$ operation.

The SN74AUC1G32 device performs the Boolean function $Y = A + B$ or $Y = \overline{\overline{A} \cdot \overline{B}}$ in positive logic.

NanoFree™ package technology is a major breakthrough in IC packaging concepts, using the die as the package.

This device is fully specified for partial-power-down applications using $I_{off}$. The $I_{off}$ circuitry disables the outputs, preventing damaging current backflow through the device when it is powered down.


For more information about AUC Little Logic devices, see *Applications of Texas Instruments AUC Sub-1-V Little Logic Devices*, SCEA027.

**Device Information**[1]

| PART NUMBER | PACKAGE | BODY SIZE (NOM) |
|---|---|---|
| SN74AUC1G32DBV | SOT-23 (5) | 2.90 mm × 1.60 mm |
| SN74AUC1G32DCK | SC70 (5) | 2.00 mm × 1.25 mm |
| SN74AUC1G32DRL | SOT-5X3 (5) | 1.60 mm × 1.20 mm |
| SN74AUC1G32YZP | DSBGA (5) | 1.39 mm × 0.89 mm |

(1) For all available packages, see the orderable addendum at the end of the data sheet.

**Logic Diagram (Positive Logic)**




An IMPORTANT NOTICE at the end of this data sheet addresses availability, warranty, changes, use in safety-critical applications, intellectual property matters and other important disclaimers. UNLESS OTHERWISE NOTED, this document contains PRODUCTION DATA.

## Table of Contents

**1 Features** ... 1
**2 Applications** ... 1
**3 Description** ... 1
**4 Revision History** ... 2
**5 Pin Configuration and Functions** ... 3
**6 Specifications** ... 4
6.1 Absolute Maximum Ratings ... 4
6.2 ESD Ratings ... 4
6.3 Recommended Operating Conditions ... 4
6.4 Thermal Information ... 5
6.5 Electrical Characteristics ... 5
6.6 Switching Characteristics: $C_L$ = 15 pF ... 5
6.7 Switching Characteristics: $C_L$ = 30 pF ... 5
6.8 Operating Characteristics ... 6
**7 Parameter Measurement Information** ... 7
**8 Detailed Description** ... 8
8.1 Functional Block Diagram ... 8
8.2 Device Functional Modes ... 8
**9 Device and Documentation Support** ... 9
9.1 Documentation Support ... 9
9.2 Receiving Notification of Documentation Updates ... 9
9.3 Community Resources ... 9
9.4 Trademarks ... 9
9.5 Electrostatic Discharge Caution ... 9
9.6 Glossary ... 9
**10 Mechanical, Packaging, and Orderable Information** ... 9

## 4 Revision History

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

**Changes from Revision O (September 2009) to Revision P** — **Page**

- Added *Application* section, *Pin Configuration and Functions* section, *ESD Ratings* table, *Feature Description* section, *Device Functional Modes*, *Application and Implementation Power Supply Recommendations* section, *Layout* section, *Device and Documentation Support* section, and *Mechanical, Packaging, and Orderable Information* section. ... 1
- Deleted *Ordering Information* table, see *Mechanical, Packaging, and Orderable Information* at the end of the data sheet. 1
- Deleted DRY package throughout data sheet ... 1


**Changes from Revision N (September 2001) to Revision O** — **Page**

- Updated document to new TI data sheet format - no specification changes. ... 1
- Removed *Ordering Information*. ... 1



Copyright © 2001–2017, Texas Instruments Incorporated

# 5 Pin Configuration and Functions


**DBV Package**
**SOT-23**
**Top View**





**DRL Package**
**5-Pin SOT-5X3**
**Top View**




**DCK Package**
**5-Pin SC70**
**Top View**




**YZP Package**
**5-Pin DSBGA**
**Bottom View**




See mechanical drawings for dimensions.

NC No internal connections

**Pin Functions**

| PIN | | | I/O | DESCRIPTION |
|---|---|---|---|---|
| NAME | DBV, DCK, DRL | YZP | | |
| A | 1 | A1 | I | Input A |
| B | 2 | B1 | I | Input B |
| GND | 3 | C1 | — | Ground |
| $V_{CC}$ | 5 | A2 | — | Positive Supply |
| Y | 4 | C2 | O | Output Y |

Copyright © 2001–2017, Texas Instruments Incorporated

# 6 Specifications

## 6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted)(1)

| | | | MIN | MAX | UNIT |
|---|---|---|---|---|---|
| $V_{CC}$ | Supply voltage | | –0.5 | 3.6 | V |
| $V_I$ | Input voltage(2) | | –0.5 | 3.6 | V |
| $V_O$ | Voltage range applied to any output in the high-impedance or power-off state(2) | | –0.5 | 3.6 | V |
| $V_O$ | Output voltage range(2) | | –0.5 | $V_{CC}$ + 0.5 | V |
| $I_{IK}$ | Input clamp current | $V_I$ < 0 | | –50 | mA |
| $I_{OK}$ | Output clamp current | $V_O$ < 0 | | –50 | mA |
| $I_O$ | Continuous output current | | | ±20 | mA |
| | Continuous current through $V_{CC}$ or GND | | | ±100 | mA |
| $T_{stg}$ | Storage temperature | | –65 | 150 | °C |

(1) Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions*. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
(2) The input negative-voltage and output voltage ratings may be exceeded if the input and output current ratings are observed.

## 6.2 ESD Ratings

| | | | VALUE | UNIT |
|---|---|---|---|---|
| $V_{(ESD)}$ | Electrostatic discharge | Human body model (HBM), per ANSI/ESDA/JEDEC JS-001(1) | ±2000 | V |
| | | Charged device model (CDM), per JEDEC specification JESD22-C101(2) | ±1000 | |

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.
(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

## 6.3 Recommended Operating Conditions

See (1)

| | | | MIN | MAX | UNIT |
|---|---|---|---|---|---|
| $V_{CC}$ | Supply voltage | | 0.8 | 2.7 | V |
| $V_I$ | Input voltage | | 0 | 3.6 | V |
| $V_O$ | Output voltage | | 0 | $V_{CC}$ | V |
| $V_{IH}$ | High-level input voltage | $V_{CC}$ = 0.8 V | $V_{CC}$ | | V |
| | | $V_{CC}$ = 1.1 V to 1.95 V | 0.65 × $V_{CC}$ | | |
| | | $V_{CC}$ = 2.3 V to 2.7 V | 1.7 | | |
| $V_{IL}$ | Low-level input voltage | $V_{CC}$ = 0.8 V | | 0 | V |
| | | $V_{CC}$ = 1.1 V to 1.95 V | | 0.35 × $V_{CC}$ | |
| | | $V_{CC}$ = 2.3 V to 2.7 V | | 0.7 | |
| $I_{OH}$ | High-level output current | $V_{CC}$ = 0.8 V | | –0.7 | mA |
| | | $V_{CC}$ = 1.1 V | | –3 | |
| | | $V_{CC}$ = 1.4 V | | –5 | |
| | | $V_{CC}$ = 1.65 V | | –8 | |
| | | $V_{CC}$ = 2.3 V | | –9 | |
| $I_{OL}$ | Low-level output current | $V_{CC}$ = 0.8 V | | 0.7 | mA |
| | | $V_{CC}$ = 1.1 V | | 3 | |
| | | $V_{CC}$ = 1.4 V | | 5 | |
| | | $V_{CC}$ = 1.65 V | | 8 | |
| | | $V_{CC}$ = 2.3 V | | 9 | |
| $\Delta t/\Delta v$ | Input transition rise or fall rate | | | 20 | ns/V |

(1) All unused inputs of the device must be held at $V_{CC}$ or GND to ensure proper device operation. See *Implications of Slow or Floating CMOS Inputs*, SCBA004.


Copyright © 2001–2017, Texas Instruments Incorporated

## Recommended Operating Conditions (continued)

See (1)

| | | MIN | MAX | UNIT |
|---|---|---|---|---|
| $T_A$ | Operating free-air temperature | –40 | 85 | °C |

## 6.4 Thermal Information

| THERMAL METRIC(1) | | SN74AUC1G32 | | | | UNIT |
|---|---|---|---|---|---|---|
| | | DBV | DCK | DRL | YZP | |
| | | 5 PINS | 5 PINS | 5 PINS | 5 PINS | |
| $R_{\theta JA}$ | Junction-to-ambient thermal resistance | 206 | 252 | 142 | 132 | °C/W |

(1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report.

## 6.5 Electrical Characteristics

over recommended operating free-air temperature range (unless otherwise noted)

| PARAMETER | | TEST CONDITIONS | | $V_{CC}$ | MIN | TYP(1) | MAX | UNIT |
|---|---|---|---|---|---|---|---|---|
| $V_{OH}$ | | $I_{OH}$ = –100 µA | | 0.8 V to 2.7 V | $V_{CC}$ – 0.1 | | | V |
| | | $I_{OH}$ = –0.7 mA | | 0.8 V | | 0.55 | | |
| | | $I_{OH}$ = –3 mA | | 1.1 V | 0.8 | | | |
| | | $I_{OH}$ = –5 mA | | 1.4 V | 1 | | | |
| | | $I_{OH}$ = –8 mA | | 1.65 V | 1.2 | | | |
| | | $I_{OH}$ = –9 mA | | 2.3 V | 1.8 | | | |
| $V_{OL}$ | | $I_{OL}$ = 100 µA | | 0.8 V to 2.7 V | | | 0.2 | V |
| | | $I_{OL}$ = 0.7 mA | | 0.8 V | | 0.25 | | |
| | | $I_{OL}$ = 3 mA | | 1.1 V | | | 0.3 | |
| | | $I_{OL}$ = 5 mA | | 1.4 V | | | 0.4 | |
| | | $I_{OL}$ = 8 mA | | 1.65 V | | | 0.45 | |
| | | $I_{OL}$ = 9 mA | | 2.3 V | | | 0.6 | |
| $I_I$ | A or B input | $V_I$ = $V_{CC}$ or GND | | 0 to 2.7 V | | | ±5 | µA |
| $I_{off}$ | | $V_I$ or $V_O$ = 2.7 V | | 0 | | | ±10 | µA |
| $I_{CC}$ | | $V_I$ = $V_{CC}$ or GND, | $I_O$ = 0 | 0.8 V to 2.7 V | | | 10 | µA |
| $C_i$ | | $V_I$ = $V_{CC}$ or GND | | 2.5 V | | 4 | | pF |

(1) All typical values are at $T_A$ = 25°C.

## 6.6 Switching Characteristics: $C_L$ = 15 pF

over recommended operating free-air temperature range, $C_L$ = 15 pF (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CC}$ = 0.8 V | $V_{CC}$ = 1.2 V ± 0.1 V | | $V_{CC}$ = 1.5 V ± 0.1 V | | $V_{CC}$ = 1.8 V ± 0.15 V | | | $V_{CC}$ = 2.5 V ± 0.2 V | | UNIT |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | TYP | MIN | MAX | MIN | MAX | MIN | TYP | MAX | MIN | MAX | |
| $t_{pd}$ | A or B | Y | 4.8 | 1 | 3.5 | 0.6 | 2.3 | 0.5 | 0.9 | 1.5 | 0.3 | 1.4 | ns |

## 6.7 Switching Characteristics: $C_L$ = 30 pF

over recommended operating free-air temperature range, $C_L$ = 30 pF (unless otherwise noted) (see Figure 1)

| PARAMETER | FROM (INPUT) | TO (OUTPUT) | $V_{CC}$ = 1.8 V ± 0.15 V | | | $V_{CC}$ = 2.5 V ± 0.2 V | | UNIT |
|---|---|---|---|---|---|---|---|---|
| | | | MIN | TYP | MAX | MIN | MAX | |
| $t_{pd}$ | A or B | Y | 0.8 | 1.4 | 2.4 | 0.6 | 2.1 | ns |


## 6.8 Operating Characteristics

$T_A$ = 25°C

| PARAMETER | | TEST CONDITIONS | $V_{CC}$ = 0.8 V | $V_{CC}$ = 1.2 V | $V_{CC}$ = 1.5 V | $V_{CC}$ = 1.8 V | $V_{CC}$ = 2.5 V | UNIT |
|---|---|---|---|---|---|---|---|---|
| | | | TYP | TYP | TYP | TYP | TYP | |
| $C_{pd}$ | Power dissipation capacitance | f = 10 MHz | 14 | 14 | 15 | 15 | 20 | pF |


Copyright © 2001–2017, Texas Instruments Incorporated


# 7 Parameter Measurement Information





LOAD CIRCUIT

| TEST | S1 |
|---|---|
| $t_{PLH}/t_{PHL}$ | Open |
| $t_{PLZ}/t_{PZL}$ | 2 × $V_{CC}$ |
| $t_{PHZ}/t_{PZH}$ | GND |


| $V_{CC}$ | $C_L$ | $R_L$ | $V_\Delta$ |
|---|---|---|---|
| 0.8 V | 15 pF | 2 kΩ | 0.1 V |
| 1.2 V ± 0.1 V | 15 pF | 2 kΩ | 0.1 V |
| 1.5 V ± 0.1 V | 15 pF | 2 kΩ | 0.1 V |
| 1.8 V ± 0.15 V | 15 pF | 2 kΩ | 0.15 V |
| 2.5 V ± 0.2 V | 15 pF | 2 kΩ | 0.15 V |
| 1.8 V ± 0.15 V | 30 pF | 1 kΩ | 0.15 V |
| 2.5 V ± 0.2 V | 30 pF | 500 Ω | 0.15 V |





VOLTAGE WAVEFORMS
PULSE DURATION




VOLTAGE WAVEFORMS
SETUP AND HOLD TIMES




VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES
INVERTING AND NONINVERTING OUTPUTS




VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES
LOW- AND HIGH-LEVEL ENABLING

NOTES: A. $C_L$ includes probe and jig capacitance.
B. Waveform 1 is for an output with internal conditions such that the output is low, except when disabled by the output control. Waveform 2 is for an output with internal conditions such that the output is high, except when disabled by the output control.
C. All input pulses are supplied by generators having the following characteristics: PRR ≤ 10 MHz, $Z_O$ = 50 Ω, slew rate ≥ 1 V/ns.
D. The outputs are measured one at a time, with one transition per measurement.
E. $t_{PLZ}$ and $t_{PHZ}$ are the same as $t_{dis}$.
F. $t_{PZL}$ and $t_{PZH}$ are the same as $t_{en}$.
G. $t_{PLH}$ and $t_{PHL}$ are the same as $t_{pd}$.
H. All parameters and waveforms are not applicable to all devices.

**Figure 1. Load Circuit and Voltage Waveforms**

Copyright © 2001–2017, Texas Instruments Incorporated

# 8 Detailed Description

## 8.1 Functional Block Diagram





**Figure 2. Logic Diagram (Positive Logic)**

## 8.2 Device Functional Modes

Table 1 lists the functional modes of SN74AUC1G32.

**Table 1. Function Table (Each Inverter)**

| INPUTS | | OUTPUT |
|---|---|---|
| A | B | Y |
| H | X | H |
| X | H | H |
| L | L | L |


Copyright © 2001–2017, Texas Instruments Incorporated

# 9 Device and Documentation Support

## 9.1 Documentation Support

### 9.1.1 Related Documentation

For related documentation see the following:

- *Applications of Texas Instruments AUC Sub-1-V Little Logic Devices*, SCEA027
- *Implications of Slow or Floating CMOS Inputs*, SCBA004

## 9.2 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. In the upper right corner, click on *Alert me* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

## 9.3 Community Resources

The following links connect to TI community resources. Linked contents are provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

**TI E2E™ Online Community** ***TI's Engineer-to-Engineer (E2E) Community.*** Created to foster collaboration among engineers. At e2e.ti.com, you can ask questions, share knowledge, explore ideas and help solve problems with fellow engineers.

**Design Support** ***TI's Design Support*** Quickly find helpful E2E forums along with design support tools and contact information for technical support.

## 9.4 Trademarks

NanoFree, E2E are trademarks of Texas Instruments.
All other trademarks are the property of their respective owners.

## 9.5 Electrostatic Discharge Caution

This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

## 9.6 Glossary

SLYZ022 — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

# 10 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

Copyright © 2001–2017, Texas Instruments Incorporated

## PACKAGING INFORMATION

| Orderable part number | Status (1) | Material type (2) | Package \| Pins | Package qty \| Carrier | RoHS (3) | Lead finish/ Ball material (4) | MSL rating/ Peak reflow (5) | Op temp (°C) | Part marking (6) |
|---|---|---|---|---|---|---|---|---|---|
| SN74AUC1G32DBVR | Active | Production | SOT-23 (DBV) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU \| SN | Level-1-260C-UNLIM | -40 to 85 | (U32F, U32R) |
| SN74AUC1G32DBVR.B | Active | Production | SOT-23 (DBV) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | (U32F, U32R) |
| SN74AUC1G32DBVRG4 | Active | Production | SOT-23 (DBV) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | U32F |
| SN74AUC1G32DBVRG4.B | Active | Production | SOT-23 (DBV) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | U32F |
| SN74AUC1G32DCKR | Active | Production | SC70 (DCK) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | (UG5, UGF, UGR) |
| SN74AUC1G32DCKR.B | Active | Production | SC70 (DCK) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | (UG5, UGF, UGR) |
| SN74AUC1G32DCKRG4 | Active | Production | SC70 (DCK) \| 5 | 3000 \| LARGE T&R | Yes | NIPDAU | Level-1-260C-UNLIM | -40 to 85 | (UG5, UGF, UGR) |
| SN74AUC1G32DRLR | Active | Production | SOT-5X3 (DRL) \| 5 | 4000 \| LARGE T&R | Yes | NIPDAUAG | Level-1-260C-UNLIM | -40 to 85 | (UG7, UGR) |
| SN74AUC1G32DRLR.B | Active | Production | SOT-5X3 (DRL) \| 5 | 4000 \| LARGE T&R | Yes | NIPDAUAG | Level-1-260C-UNLIM | -40 to 85 | (UG7, UGR) |
| SN74AUC1G32YZPR | Active | Production | DSBGA (YZP) \| 5 | 3000 \| LARGE T&R | Yes | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | UGN |
| SN74AUC1G32YZPR.B | Active | Production | DSBGA (YZP) \| 5 | 3000 \| LARGE T&R | Yes | SNAGCU | Level-1-260C-UNLIM | -40 to 85 | UGN |

(1) **Status:** For more details on status, see our product life cycle.

(2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

(3) **RoHS values:** Yes, No, RoHS Exempt. See the TI RoHS Statement for additional information and value definition.

(4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

(5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

(6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.


Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.


In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## TAPE AND REEL INFORMATION

**REEL DIMENSIONS**





**TAPE DIMENSIONS**




| | |
|---|---|
| A0 | Dimension designed to accommodate the component width |
| B0 | Dimension designed to accommodate the component length |
| K0 | Dimension designed to accommodate the component thickness |
| W | Overall width of the carrier tape |
| P1 | Pitch between successive cavity centers |


**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**




*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 180.0 | 8.4 | 3.23 | 3.17 | 1.37 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 178.0 | 9.0 | 3.23 | 3.17 | 1.37 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 180.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 180.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DBVRG4 | SOT-23 | DBV | 5 | 3000 | 178.0 | 9.0 | 3.23 | 3.17 | 1.37 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DBVRG4 | SOT-23 | DBV | 5 | 3000 | 180.0 | 8.4 | 3.2 | 3.2 | 1.4 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DCKR | SC70 | DCK | 5 | 3000 | 180.0 | 8.4 | 2.47 | 2.3 | 1.25 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DCKR | SC70 | DCK | 5 | 3000 | 178.0 | 9.2 | 2.4 | 2.4 | 1.22 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DCKR | SC70 | DCK | 5 | 3000 | 178.0 | 9.0 | 2.4 | 2.5 | 1.2 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32DRLR | SOT-5X3 | DRL | 5 | 4000 | 180.0 | 8.4 | 1.98 | 1.78 | 0.69 | 4.0 | 8.0 | Q3 |
| SN74AUC1G32YZPR | DSBGA | YZP | 5 | 3000 | 178.0 | 9.2 | 1.02 | 1.52 | 0.63 | 4.0 | 8.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS




*All dimensions are nominal


| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|---|---|---|---|---|---|---|---|
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 202.0 | 201.0 | 28.0 |
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 210.0 | 185.0 | 35.0 |
| SN74AUC1G32DBVR | SOT-23 | DBV | 5 | 3000 | 210.0 | 185.0 | 35.0 |
| SN74AUC1G32DBVRG4 | SOT-23 | DBV | 5 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74AUC1G32DBVRG4 | SOT-23 | DBV | 5 | 3000 | 210.0 | 185.0 | 35.0 |
| SN74AUC1G32DCKR | SC70 | DCK | 5 | 3000 | 202.0 | 201.0 | 28.0 |
| SN74AUC1G32DCKR | SC70 | DCK | 5 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74AUC1G32DCKR | SC70 | DCK | 5 | 3000 | 180.0 | 180.0 | 18.0 |
| SN74AUC1G32DRLR | SOT-5X3 | DRL | 5 | 4000 | 202.0 | 201.0 | 28.0 |
| SN74AUC1G32YZPR | DSBGA | YZP | 5 | 3000 | 220.0 | 220.0 | 35.0 |

# PACKAGE OUTLINE

## DBV0005A

## SOT-23 - 1.45 mm max height


SMALL OUTLINE TRANSISTOR





4214839/K 08/2024

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Refernce JEDEC MO-178.
4. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25 mm per side.
5. Support pin may differ or may not be present.




LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:15X





SOLDER MASK DETAILS

4214839/K 08/2024

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SOLDER PASTE EXAMPLE
BASED ON 0.125 mm THICK STENCIL
SCALE:15X

4214839/K 08/2024

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

# PACKAGE OUTLINE

## DRL0005A

## SOT - 0.6 mm max height


PLASTIC SMALL OUTLINE





4220753/E 11/2024

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. Reference JEDEC registration MO-293 Variation UAAD-1




LAND PATTERN EXAMPLE
SCALE:30X





SOLDERMASK DETAILS

4220753/E 11/2024

NOTES: (continued)

5. Publication IPC-7351 may have alternate designs.
6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:30X

4220753/E 11/2024

NOTES: (continued)


7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.

# PACKAGE OUTLINE

## YZP0005

## DSBGA - 0.5 mm max height

DIE SIZE BALL GRID ARRAY





D: Max = 1.418 mm, Min =1.358 mm

E: Max = 0.918 mm, Min =0.858 mm


4219492/A 05/2017

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.




LAND PATTERN EXAMPLE
SCALE:40X





SOLDER MASK DETAILS
NOT TO SCALE

4219492/A 05/2017

NOTES: (continued)

3. Final dimensions may vary due to manufacturing tolerance considerations and also routing constraints. For more information, see Texas Instruments literature number SNVA009 (www.ti.com/lit/snva009).




SOLDER PASTE EXAMPLE
BASED ON 0.1 mm THICK STENCIL
SCALE:40X

4219492/A 05/2017

NOTES: (continued)


4. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release.

# PACKAGE OUTLINE

## DCK0005A

## SOT - 1.1 max height


SMALL OUTLINE TRANSISTOR





4214834/G 11/2024

NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Refernce JEDEC MO-203.
4. Support pin may differ or may not be present.
5. Lead width does not comply with JEDEC.
6. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.25mm per side




LAND PATTERN EXAMPLE
EXPOSED METAL SHOWN
SCALE:18X





SOLDER MASK DETAILS

4214834/G 11/2024

NOTES: (continued)

7. Publication IPC-7351 may have alternate designs.
8. Solder mask tolerances between and around signal pads can vary based on board fabrication site.




SOLDER PASTE EXAMPLE
BASED ON 0.125 THICK STENCIL
SCALE:18X

4214834/G 11/2024

NOTES: (continued)

9. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
10. Board assembly site may have different recommendations for stencil design.

# IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI’s products are provided subject to TI’s Terms of Sale, TI’s General Quality Guidelines, or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI’s provision of these resources does not expand or otherwise alter TI’s applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2026, Texas Instruments Incorporated

Last updated 10/2025