

RoHS





USB TYPE-C PIN ASSIGNMENTS


PIN	Signal Name		PIN	Signal Name
A1	GND		B12	GND
A2	SSTXp1		B11	SSRXp1
A3	SSTXn1		B10	SSRXn1
A4	VBUS		B9	VBUS
A5	CC1		B8	SBU2
A6	Dp1		B7	Dn2
A7	Dn1		B6	Dp2
A8	SBU1		B5	CC2
A9	VBUS		B4	VBUS
A10	SSRXn2		B3	SSTXn2
A11	SSRXp2		B2	SSTXp2
A12	GND		B1	GND

REV.	ECN.#	DESCRIPTION	NAME	DATE
A0	————	NEW RELEASE	liuhongping	2023.01.02










RECOMMENDED PCB LAYOUT(TOP VIEW)

NOTES:
1. MATERIAL:
   1.1 HOUSING: LCP UL94V-0; COLOR: BLACK
   1.2 TERMINAL: C7025
   1.3 SHELL: SUS304
   1.4 MID PLATE: SUS301
   1.5 EMC: SUS316
2. FINISH:
   2.1 TERMINAL: G/F PLATED ON CONTACT AREA;
   G/F PLATED ON SOLDER AREA;
   Ni 20u" MIN. UNDERPLATED OVERALL.
   2.2 SHELL: Ni 20u" MIN. PLATED OVERALL
   2.3 MID PLATE/EMC: CLEANING.
3. ELECTRICAL SPECIFICATION:
   3.1 RATED CURRENT: VBUS AND GND PIN 5.0A;
   Other pin 0.25A
   3.3 CONTACT RESISTANCE: 40mΩ MAX(INITIAL). 50mΩ MAX (AFTER).
   3.4 INSULATION RESISTANCE: 100MΩ MIN.
   3.5 DIELECTRIC WITHSTANDING VOLTAGE: 100V AC R.M.S.
4. MACHINERY SPECIFICATION:
   4.1 MATING FORCE: 5N~20N.
   UNMATING FORCE: 8N~20N. (AFTER TEST:6N~20N).
   4.2 DURABILITY: 10000 CYCLES MIN.
5. ENVIRONMENTAL SPECIFICATION:
   5.1 OPERATING CONDITION: TEMPERATURE-40℃~+85℃;
   HUMIDITY 80% R.H MAX
   5.2 SALT SPRAY: 24H
6. SOLDER ABILITY: 245±5℃, 5±0.5s
7. IR REFLOW: THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260℃.




MILLIMETERS	INCH
X.° ±2°	X.° ±2°
.X ±0.30	.X ±0.012
.XX ±0.20	.XX ±0.008
.XXX ±0.10	.XXX ±0.004


THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DongGuan JinBiLai Metal Plastic Technology Co.?Ltd
COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DongGuan JinBiLai Metal Plastic Technology Co.,Ltd

东莞市金比莱五金塑胶科技有限公司
DONGGUAN JBL TECH CO., LTD

TITLE	TYPE C 24PIN 板上双SMT L7.90 带柱				DR	
PART NO.	104311002-A				CHKD	
PRO J.	PAGE	1/2	UNITS	mm	APPD	
	SIZE	A4	SCALE	1:1	DIS NO.	


RoHS







NOTES

1. NUMBER OF CONNECTORS: 1000PCS/REEL
2. LEAD TAPE LENGTH



3.QUANTITY: 10000PCS/CARTON





MILLIMETERS	INCH
X.° ±2°	X.° ±2°
.X ±0.30	.X ±0.012
.XX ±0.20	.XX ±0.008
.XXX ±0.10	.XXX ±0.004

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DongGuan JinBiLai Metal Plastic Technology Co.?Ltd
COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DongGuan JinBiLai Metal Plastic Technology Co.,Ltd

东莞市金比莱五金塑胶科技有限公司
DONGGUAN JBL TECH CO.,LTD

TITLE	TYPE C 24PIN 板上双SMT L7.90 带柱				DR		
PART NO.	104311002-A				CHKD		
PRO J.	PAGE	2/2	UNITS	mm	APPD		
	SIZE	A4	SCALE	1:1	DIS NO.		