
MMBTA06 TRANSISTOR (NPN)

FEATURES

- For Switching and Amplifier Applications
- Complementary Type PNP Transistor MMBTA56

SOT-23



1. BASE
2. EMITTER
3. COLLECTOR

MARKING: 1GM


MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)


Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	80	V
V_{CEO}	Collector-Emitter Voltage	80	V
V_{EBO}	Emitter-Base Voltage	4	V
I_C	Collector Current	500	mA
P_C	Collector Power Dissipation	300	mW
$R_{\Theta JA}$	Thermal Resistance From Junction To Ambient	417	℃/W
T_j	Junction Temperature	-55～+150	℃
T_{stg}	Storage Temperature	-55～+150	℃


ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=0.1mA, I_E=0	80			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=1mA, I_B=0	80			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=0.1mA, I_C=0	4			V
Collector cut-off current	I_{CBO}	V_{CB}=80V, I_E=0			0.1	μA
Collector cut-off current	I_{CEO}	V_{CE}=60V, I_B=0			1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=3V, I_C=0			0.1	μA
DC current gain	$h_{FE(1)}$	V_{CE}=1V, I_C=10mA	100		400	
	$h_{FE(2)}$	V_{CE}=1V, I_C=100mA	100			
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=100mA, I_B=10mA			0.25	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=100mA, I_B=10mA			1.2	V
Transition frequency	f_T	V_{CE}=2V, I_C=10mA, f=100MHz	100			MHz


Typical Characteristics





















PACKAGE OUTLINE

SOT-23



UNIT	A	B	bp	C	D	E	HE	A1	Lp
mm	1.40 0.89	2.04 1.78	0.51 0.30	0.19 0.08	3.10 2.70	1.65 1.20	3.00 2.20	0.100 0.013	0.50 0.20