

DATASHEET

4 PIN DIP HIGH VOLTAGE PHOTODARLINGTON PHOTOCOUPLER
EL852 Series



Schematic



Pin Configuration
1. Anode
2. Cathode
3. Emitter
4. Collector

Features:

- Compliance Halogens Free (Only copper leadframe) (Br < 900 ppm, Cl < 900 ppm, Br+Cl < 1500 ppm)
- High collector- emitter voltage (VCEO=350V)
- Current transfer ratio (CTR: 1000% min. at I_F =1mA, V_{CE} =2V)
- High isolation voltage between input and output (Viso=5000 V rms)
- Creepage distance >7.62 mm
- Operating temperature up to +100°C
- Compact small outline package
- Pb free and RoHS compliant.
- UL and cUL approved(No. E214129)
- VDE approved
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CQC approved

Description

The EL852 series consists an infrared emitting diodes, optically coupled to a high voltage photo Darlington detector.
It is packaged in a 4-pin DIP package and available in wide-lead spacing and SMD option.

Applications

- Telephone set, telephone exchangers
- Sequence controllers
- System appliances, measuring instruments
- Signal transmission between circuits of different potentials and impedances

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9

Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Absolute Maximum Ratings (Ta=25℃)

Parameter		Symbol	Rating	Unit
Input	Forward current	I_F	60	mA
	Peak forward current (1us, pulse)	I_{FP}	1	A
	Reverse voltage	V_R	6	V
	Power dissipation No derating required up to Ta = 100°C	P_D	100	mW
Output	Power dissipation	P_C	300	mW
	Derating factor (above Ta = 80°C)		5.8	mW/°C
	Collector current	I_C	150	mA
	Collector-Emitter voltage	V_{CEO}	350	V
	Emitter-Collector voltage	V_{ECO}	0.1	V
Total power dissipation		P_{TOT}	320	mW
Isolation voltage *1		V_{ISO}	5000	V rms
Operating temperature		T_{OPR}	-55 ~ +100	°C
Storage temperature		T_{STG}	-55 ~ +125	°C
Soldering Temperature*2		T_{SOL}	260	°C

Notes:
*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1 & 2 are shorted together, and pins 3 & 4 are shorted together.

*2 For 10 seconds

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9

Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Electro-Optical Characteristics (Ta=25℃ unless specified otherwise)

Input

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Forward Voltage	V_F	-	1.2	1.4	V	I_F = 10mA
Reverse Current	I_R	-	-	10	μA	V_R = 4V
Input capacitance	C_{in}	-	30	250	pF	V = 0, f = 1kHz

Output

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Collector-Emitter dark current	I_{CEO}	-	-	200	nA	V_{CE} = 200V, I_F = 0mA
Collector-Emitter breakdown voltage	BV_{CEO}	350	-	-	V	I_C = 0.1mA
Emitter-Collector breakdown voltage	BV_{ECO}	0.1	-	-	V	I_E = 0.1mA

Transfer Characteristics

Parameter	Symbol	Min.	Typ.*	Max.	Unit	Condition
Current Transfer ratio	CTR	1000	-	15000	%	I_F = 1mA ,V_{CE} = 2V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	-	-	1.2	V	I_F = 20mA ,I_C = 100mA
Isolation resistance	R_{IO}	5×10^{10}	-	-	Ω	V_{IO} = 500Vdc, 40~60% R.H.
Floating capacitance	C_{IO}	-	0.6	1.0	pF	V_{IO} = 0, f = 1MHz
Cut-off frequency	fc	-	7	-	kHz	V_{CE} = 2V, I_C = 20mA R_L = 100Ω, -3dB
Rise time	t_r	-	-	300	μs	V_{CE} = 2V, I_C = 20mA, R_L = 100Ω
Fall time	t_f	-	-	100	μs	

* Typical values at T_a = 25°C

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Typical Electro-Optical Characteristics Curves

Figure 1. Forward Current vs. Forward Voltage




Figure 2. Collector Current vs. Collector Emitter Voltage




Figure 3. Collector Emitter Saturation Voltage vs. Ambient Temperature




Figure 4. Collector-Emitted Saturation Voltage vs. Forward Current




Figure 5. Current Transfer Ratio vs. Forward Current





Figure 6. Normalized Current Transfer Ratio vs. Ambient Temperature



Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Figure 7. Collector Dark Current vs. Ambient Temperature




Figure 8. Response Time vs. Load Resistance





Figure 9. Frequency Response



Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Order Information

Part Number

EL852X(Y)-V

Note

X = Lead form option (S, S1, S2, M or none)
Y = Tape and reel option (TA, TB ,TU, TD or none).
V = VDE safety (optional).


Option	Description	Packing quantity
None	Standard DIP-4	100 units per tube
M	Wide lead bend (0.4 inch spacing)	100 units per tube
S (TA)	Surface mount lead form + TA tape & reel option	1000 units per reel
S (TB)	Surface mount lead form + TB tape & reel option	1000 units per reel
S1 (TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S1 (TB)	Surface mount lead form (low profile) + TB tape & reel option	1000 units per reel
S2 (TA)	Surface mount lead form (Gull-wing) + TA tape & reel option	1000 units per reel
S2 (TB)	Surface mount lead form (Gull-wing) + TB tape & reel option	1000 units per reel
S (TU)	Surface mount lead form + TU tape & reel option	1500 units per reel
S (TD)	Surface mount lead form + TD tape & reel option	1500 units per reel
S1 (TU)	Surface mount lead form (low profile) + TU tape & reel option	1500 units per reel
S1 (TD)	Surface mount lead form (low profile) + TD tape & reel option	1500 units per reel

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9


Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Package Dimension (Dimensions in mm)

Standard DIP Type




Option M Type




Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9

Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Option S Type




Option S1 Type



Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9

Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Option S2 Type




EVERLIGHT


Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Recommended pad layout for surface mount leadform


For S option



For S1option



For S2 option



Notes

Suggested pad dimension is just for reference only.
Please modify the pad dimension based on individual need.

Device Marking



Notes


EL	denotes EVERLIGHT
852	denotes Device Number
Y	denotes 1 digit Year code
WW	denotes 2 digit Week code
V	denotes VDE optional

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9

Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Tape & Reel Packing Specifications


Option TA




Direction of feed from reel




Option TB



Direction of feed from reel



Tape dimensions




Dimension No.	A	B	Do	D1	E	F
Dimension (mm) S	10.7±0.1	4.65±0.1	1.5±0.1	1.50±0.1	1.75±0.1	7.5±0.1
Dimension (mm) S1	10.7±0.1	4.65±0.1	1.5±0.1	1.50±0.1	1.75±0.1	7.5±0.1
Dimension (mm) S2	12.15±0.1	4.65±0.1	1.5±0.1	1.50±0.1	1.75±0.1	7.5±0.1

Dimension No.	Po	P1	P2	t	W	K
Dimension (mm) S	4.0±0.1	12.0±0.1	2.0±0.1	0.4±0.1	16.0±0.3	4.75±0.1
Dimension (mm) S1	4.0±0.1	12.0±0.1	2.0±0.1	0.4±0.1	16.0±0.3	3.90±0.1
Dimension (mm) S2	4.0±0.1	16.0±0.1	2.0±0.1	0.4±0.1	16.0±0.3	3.90±0.1

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)


Tape & Reel Packing Specifications

Option TD




Direction of feed from reel

Option TU



Direction of feed from reel

Tape dimensions




Dimension No.	Ao	Bo	Do	D1	E	F
Dimension (mm) S.S1	4.90±0.1	10.40±0.1	1.5±0.1	1.50±0.1	1.75±0.1	7.50±0.1
Dimension No.	**Po**	**P1**	**P2**	**t**	**W**	**Ko**
Dimension (mm) S.S1	4.00±0.1	8.00±0.	2.00±0.1	0.40±0.1	16.00±0.3	4.60±0.1

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

Precautions for Use

1. Soldering Condition

1.1 (A) Maximum Body Case Temperature Profile for evaluation of Reflow Profile



Note: Reference: IPC/JEDEC J-STD-020D

Preheat	
Temperature min (T_{smin})	150 °C
Temperature max (T_{smax})	200°C
Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds
Average ramp-up rate (T_{smax} to T_p)	3 °C/second max
Other	
Liquidus Temperature (T_L)	217 °C
Time above Liquidus Temperature (t_L)	60-100 sec
Peak Temperature (T_P)	260°C
Time within 5 °C of Actual Peak Temperature: T_P - 5°C	30 s
Ramp- Down Rate from Peak Temperature	6°C /second max.
Time 25°C to peak temperature	8 minutes max.
Reflow times	3 times

.

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9
Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)

DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
3. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
4. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.
5. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.
6. Statements regarding the suitability of products for certain types of applications are based on Everlight's knowledge of typical requirements that are often placed on Everlight products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Everlight's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Copyright © 2010, Everlight All Rights Reserved. Release Date : Oct 24, 2018. Issue No: DPC-0000056 Rev. 9

Ver.:9 Release Date:10/29/2018 狀態:Approved(正式發行)